NETUM®

Product introduction:

1. Foldable rotating fuselage, compact and easy to carry.

2. Can adjust multiple joints, bent, selfie back, arbitrary side shot.

3. Type-C power supply interface, without external power supply, high-speed and high-quality data transmission.

4. Applicable to multiple application scenarios: corporate documents, contract bills scanning, archive room, fast scanning archives electronic archiving, materials, campus class, test paper textbook display, online teaching, remote calligraphy, painting training, video shooting, video recording, photo sharing, and so on, in addition to support a variety of live communication software.

Product	Video Camera Platform
Imaging Sensor	12M 1/2.8" CMOS Sensor
Resolution	4000*3000@15fps,4K、2K@30fps/1080P@30fps
Image Processing	High Performance ISP
Power Input	DC5V 500mA, Type-C interface (DC supply)
Camera Lens	6P, FF, distortion <6% DFOV=79 degrees
Aperture	F1.8
Focusing	PDAF, phase focusing, focusing time about 0.4 seconds
Depth of Field	10cm~Infinity
CCM Size	8.5*8.5*6mm(The specific module shall prevail)
Image Quality Adjustment	Automatic (default)
Anti-flicker	Support 50HZ / 60HZ
Mirror Image	Support
E-PTZ	E-PTZ (1080P or lower resolution)

Image Quality Enhancement	2D noise reduction
USB takes	USB takes photos up to 12 megapixels
Audio	Optional: UAC Standard
UVC Video	UVC, compatible with Windlows, MAC OS, Linux and Android MJPG： 4000x3000@15fps 3840x2160@30fps 2592x1944@30fps 2048x1536@30fps 1920x1080@30fps 1280x720@30fps 800x 600@30fps 640x480@30fps
USB Port	USB2.0 port, UVC/UAC standard protocol, powered by USB
Others	Extensible custom UVC directives
Appearance	Folding type, plastic case + metal aluminum parts
Measure	L * W * H: 190*110*618 (mm)
Weight	1.286kg