

## NT-1208 Wired laser barcode scanner



### Features

1. Super decoding ability
2. Decoding rate: 280 times per second
3. Customer setting: Barcode setting mode, easy to operate
4. Full independent intellectual property right
5. Intelligent AGC control
6. Antiknock, full quakeproof design, withstand 7m drops
7. Comfortable button, service life of button up to 5million times

### Specifications

Type of illuminant	650nm laser ( safe visible light )
Supported interfaces	USB (standard), RS232 (optional)
Decode Capability	Code 39, Full ASCII, Code bar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, Code 93, Code 128, Code 32, Standard code 39, EAN 128, MSI, EAN 8&13, UPCA & E, Plessey, Databar14, TELEPE, GSI Databar
Precision	≥3 mil (0.076 mm)
CPU	32 Bit
Depth of scan field	10-800mm
Decode speed	280 times/second
Decode error rate	Less than 1/8 million
Print Contrast Signal	≥20°
scan angle	Yaw(Skew)45° & Pitch60°
Safety	Full quakeproof, waterproof, dustproof, antiknock-design and EMI Shielding

### Electrical

Voltage	DC 5V±5%
Current	Maximum current :40mA

### Environmental

Operating temperature	0°C~+50°C
Storage temperature	20°C~70°C
Humidity	5%-95%
Certifications	CE, IP67, ROHS, FCC

### Optional:

Color : Yellow (standard) Orange (optional)



Interface : USB (standard) RS232 (optional)



### Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportations
- ✓ Postal service
- ✓ Industrial and manufacturing management

### Packing list

scanner × 1	
cable × 1	
Base(Optional) × 1	
User's guide × 1	

### Packing details

scanner	Size(L*W*H)	170mm*100mm*70mm	
	Weight	235g;	
		Without Stand	With Stand
Inner Box	1pc/box; 190mm × 115mm ×85mm; 320g	1pc/box; 210mm × 130mm ×100mm; 520g	
Carton	50 sets/ctn;33kg/ctn; 600mm×450mm×420 mm 70 sets/ctn; 33kg/ctn; 880mm×450mm× 420mm	50 sets/ctn; 33kg/ctn; 880mm×450mm× 420mm	
20FT Container	10500pcs; 150ctns 7500pcs; 150ctns	11250pcs; 225ctns	
40FT Container	23800pcs; 325ctns 16250pcs; 325ctns	25000pcs; 500ctns	

### Certifications

