

NT-2050

2D wired barcode scanner



Features

1. Operation speed, decoding ability.
2. Decoding speed of 1500 lines / sec, the real touch.
3. Customer setting : Barcode setting mode, easy to operate
4. Automatic identification of anti-white bar code: no need to set, automatic identification.Intelligent AGC control
5. Very long depth of field: 0-200mm @ (UPC / EAN 100%, PCS90%).
6. BER test : the product has passed 5 million times without error test.

Feature	
Light Resource	2D (Safe visible light)
Port/Interface	USB (standard)
Supported Symbolologies	PDF417, QRcode, Date Matrix, Maxicode, Aztec Code, HanxinCode, MicroQR, Code39, FullASCII, Codebar, Industrial 2of5, Interleave2of5, Matrix2of5, Code93, Code128, Code32, EAN 128, MSI, EAN 8&13, UPCA&E, Plessey,
Presicion	≥5mil
Depth of scan field	0-270mm
Decode Error Rate	less than 1/7 million
Print Contrast Signal	≥30°
Scan Angle	48° (H) x 30° (V)

Mechanical/ Electrical

Voltage	5VDC±10%
Current	400mA
Maximum power	1.75W

Environmetal

Operation Temperature	0℃~50℃
Storage Temperature	-20℃~70℃
Humidity	5%-95%

Optional:



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Size(L*W*H)	135mm*90mm*105mm
	Weight	465g;
	Without Stand	
Inner Box	1pc/box; 210mm*140mm*110mm; 720g	
Carton	20sets/ctn; 11.8kg/ctn; 690mm×420mm×255mm	
20FT Container	10500pcs; 150ctns 7500pcs; 150ctns	
40FT Container	23800pcs; 325ctns 16250pcs; 325ctns	

Certifications

