

NT-2055M
2D wired barcode scanner

Optional:

Features

1. Operation speed, decoding ability.
2. Supports high-performance 1D/2D barcode scanning, which is excellent for illegible barcodes with poor print quality, contamination or distortion
3. Customer setting : Barcode setting mode, easy to operate
4. HID USB HID, Virtual COM Port / RS-232 multi-interface optional
5. Very long depth of field: 0-200mm @ (UPC / EAN 100%, PCS90%).
6. Equipped with 1280 pixels(H)x 800 pixels(V) megapixel sensor.
7. All-round automatic induction trigger, able to adapt to various lighting working environments

Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportation
- ✓ Postal service
- ✓ Industrial and manufacturing management

Feature	
Light Resource	617nm red LED
Pixel	1280 pixels(H)x 800 pixels(V)
Port/Interface	USB (standard)
Supported Symbologies	1D: UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8 &JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93,Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code,MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode),RSS 14,RSS Limited, RSS Expanded 2D:Data Matrix, QR Code, Micro QR Code Aztec Code MaxiCode
Precision	0.127mm(5mil)@Code 39, PCS=90%
Depth of scan field	Code 39-5mil:60mm-120mm UPCA-13mil(100%):35mm-310mm
Decode Error Rate	0 Error
Print Contrast Signal	≥30° (UPC/EAN 100% , PCS 90%)
Scan Angle	48° (H) x 30° (V)
Mechanical/ Electrical	
Voltage	5VDC±10%
Current	400mA
Maximum power	1.75W
Environmental	
Operation Temperature	0℃~50℃
Storage Temperature	-20℃-70℃
Humidity	5%-95%

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Size(L*W*H)	135mm*90mm*105mm
	Weight	
Inner Box	1pc/box; 210mm*140mm*110mm;	
Carton	20sets/ctn; 11.8kg/ctn; 690mm×420mm×255mm	
20FT Container	10500pcs; 150ctns	
	7500pcs; 150ctns	
40FT Container	23800pcs; 325ctns	
	16250pcs; 325ctns	

Certifications
