

NT-C990
Wired & BT 2D barcode scanner



Features

1. Support to read the inversion DM bar code USB port, Plug and play
2. USB port, Plug and play
3. More deeper Depth of scan field and lower decode error rate
4. IP54 quakeproof design, within 2m drops

Feature	
Light Resource	CMOS
Resolution	1 MP (1200*800)
CPU	32 bit high resolution
Supported Symbolgies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Scans per charge	30000 times
Precision	≥ 4 mil (0.10mm)
Decode speed	5 in/s(12.7 cm)
Decode error rate	Less than 1/8 million
Depth of scan field	Code 39 30mm~180mm(5mil) Ean-13 40mm~380mm(13mil) Data Matrix 30mm~130mm(10mil) QR Code 30mm-155mm (15mil) PDF 417 40mm-125mm(6.67mil)
Print Contrast Signal	≥ 30°
scan angle	Yaw(Skew)45° & Pitch60°
Working Distance	10 meters
capacity	1200mAh
Mechanical / Electrical	
Working Voltage	3.3 VDC ±5%
Current	working 230mA Standby: 3.4mA (RS232) , 54.0mA(USB)
Rated power consumption	186mW
Environment	
Operating temperature	-20°C-45°C
Storage temperature	-20°C-45°C
Humidity	5%-85%

Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportation
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

	Weight	105*50*25mm
scanner	1pc/box; 190mm × 115mm × 85mm; 220g	100g;
Inner Box	50 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns 23800pcs; 325ctns	

Certifications

