


NT-W3
Wired CCD barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 1D codes
3. Service life of button reaches up to 8 million times.
4. Comfortable button, service life of button up to 5million times

Feature	
Light Resource	C C D (Safe visible light)
Port/Interface	USB (standard), RS232 (optional)
Supported Symbolgies	EAN-8, EAN-13, Codabar, CODE11, CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E ISBN/ISSN, ISBT, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5 MSI, Plessey, ITF14
Precision	≥4 mil/0.127mm@PCS90%
Depth of scan field	Code 39:110mm-170mm(0.127mm 5mil) Code 39:100mm-450mm(0.5mm 20mil) Code 39:240mm-480mm(1.0mm 40mil) UPC/EAN 13:100mm-250mm(0.33mm 13mil)
Battery capacity	2000MAH
Resolution	2500
Charging time	4~6 hours
Decode speed	300 times/ second
Decode Error Rate	less than 1/8 million
Print Contrast Signal	≥10°
Scan Angle	Yaw(Skew) 60° Pitch 60°

Mechanical / Electrical

Voltage	5VDC ±5%
Current	Maximum current :130mA

Environment

Operating temperature	0°C~+50°C
Storage temperature	20°C~70°C
Humidity	5%-95%
Certifications	CE, ROHS, FCC, IP54

Optional:



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cabl × 1	

Packing details

scanner	Weight	165*65*90mm
	1pc/box; 190mm × 115mm × 85mm; 260g	275g;
Inner Box	50 sets/ctn;15kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

