

NT-W8-X 2.4G Wireless 2D barcode scanner



Features

1. Fast and accurate in reading 2D codes
2. Service life of button reaches up to 8 million times.
3. Large capacity battery 2000 MAH, Solve frequent charging problems
4. Three modes: wired/ wireless/ Bluetooth
5. Mini Receiver

Feature	
Light Resource	CMOS (5600K White LED)
Supported interfaces	USB (standard), RS232 (optional)
Image	1MP(1280*800)
Supported Symboligies	2D: PDF417、Micro PDF 417, QR Code (QR1/2, Micro),Data Matrix, Aztec, Chinese Sensible Code 1D : UPC-A, UPC-E, EAN-8, EAN-13, Code128, Code39, Code 93, Code32, Code11, Codabar, Plessey, MSI, Interleaved 2 of 5, IATA 2 of 5, Matrix 2 of 5, Straight 2 of 5, Pharmacode, RSS-14, RSS-14 Expanded, RSS-14 Limited, Composite Code-A, Composite Code-B, Composite Code-C.
Precision	4 mil (0.10mm)
Charging time	4~6hour
Depth of scan field	EAN-13:50mm-365mm(13mil) Code 39:40mm-165mm(5mil) Data Matrix:35mm-115mm(10mil) QR Code:35mm-145mm(15mil) PDF 417:45mm-115mm(6.67mil)
Decode error rate	Less than 1/8 million
Print Contrast Signal	≥ 15°
scan angle	Yaw(Skew)55° & Pitch55°

Mechanical / Electrical

Working Voltage	DC3.3-4.2V ±5%
Current	working 395mA

Environment

Operating temperature	0°C~ +50°C
Storage temperature	-20°C~ +70°C
Humidity	5%-95%
Certifications	CE, IP54, ROHS, FCC

Optional:



Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportation
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Weight	165*65*90mm
	1pc/box; 190mm × 115mm × 85mm; 260g	275g;
Inner Box	50 sets/ctn;16kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

