

NT-Z2s Bluetooth 2D barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 1D codes
3. Service life of button reaches up to 8 million times.
4. Added screen display, FSTN LCD 128*64. Supports display of electricity and bar codes
5. Support for displaying Bluetooth connection status
6. Scanning barcode in addition to the buzzer ring also increased the vibration

Feature	
Light Resource	CMOS
Bluetooth Version	V 4.0 , HID mode , SPP mode
CPU	32 bit
Supported Symboligies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Charging time	3~4hour
Precision	≥ 5 mil (0.10mm)
Decode error rate	Less than 1/8 million
Depth of scan field	Code 128 60mm-200mm(10mil) QR Code 160 bytes (paper) 40mm-120mm (10mil) DM Code 100 bytes (paper) 50mm-140mm (15mil) QR Code 18 bytes (screen) 50mm-250mm (10mil)
Print Contrast Signal	≥ 15%
scan angle	Yaw(Skew)55° & Pitch55°
Working Distance	10-30meter
Battery capacity	1000MAH
Mechanical / Electrical	
Working Voltage	3.3 VDC ±5%
Current	working 370mA
Environment	
Operating temperature	0°C~+50°C
Storage temperature	-20°C~+70°C
Humidity	5%-95%

Optional:



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Weight	105*50*25mm
	1pc/box; 160mm × 100mm × 730mm; 220g	100g;
Inner Box	50 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

