Optional:

Color :

NT-Z3s

Laser blutooth barcode scanner







Features

- 1. Factory direct sale, cheap price and stable scanning
- 2. Fast and accurate in reading 1D codes
- 3. Service life of button reaches up to 8 million times.
- 4. Added screen display , FSTN LCD 128*64 . Supports display of electricity and bar codes
- 5. Support for displaying Bluetooth connection status.
- 6. Scanning barcode in addition to the buzzer ring also increased the vibration.

| Feature | | |
|-----------------------|--|--|
| Light Resource | C C D (Safe visible light) | |
| Bluetooth Version | V 4.0 , HID mode , SPP mode | |
| CPU | 32 bit high resolution | |
| Supported Symboligies | 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25 Standard 25, Code39, Codabar, Code 93, Code 11, | |
| Charging time | 3~4hour | |
| Precision | ≥ 4 mil (0.10mm) | |
| Decode speed | 200 times/second | |
| Decode error rate | Less than 1/8 million | |
| Depth of scan field | 10-800mm | |
| Print Contrast Signal | ≥ 10% | |
| scan angle | Yaw(Skew)60° & Pitch60° | |
| Battery capacity | 1000MAH | |
| | | |

Mechanical / Electrical

| - | | |
|-----------------------|-----------------------|--|
| Working Voltage | 3.3VDC ±5% | |
| Current | Maximum current :85mA | |
| Environment | | |
| Operating temperature | 0°C~+50°C | |
| Storage temperature | 20°C~70°C | |
| Humidity | 5%-95% | |

Applicable scope

Interface :

✓ Commercial POS system(Supermarkets)

White

USB cable

- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transpiration
- ✓ Postal service
- Industrial and manufacturing management

Packing list

scanner $\times 1$

User's guide \times 1

cable $\times 1$



Packing details

| scanner | Weight | 105*50*25mm |
|-------------------|--|-------------|
| | 1pc/box; 190mm × 115mm ×85mm; 220g | 100g; |
| Inner Box | 50 sets/ctn;12kg/ctn; 600mm×450mm×420mm | |
| Carton | 10500pcs; 150ctns | |
| 20FT Container | 7500pcs; 150ctns | |
| | 23800pcs; 325ctns | |



Operational Address: (Plant A1), No. 137, Taipingyang Industrial Zone, Xintang Town, Zengcheng, Guangzhou, Guangdong, China (Mainland)