Weifang Starocean Machinery and Equipment Co., Ltd.

Add: #3088 Zhaode Nanlu, Yunmenshan Street, Qingzhou, Weifang, Shandong Province, China Attn: Skylar Tel: +86 15305365593 Mail: skylar@generatorso.com Web: www.generatorso.com

Technical specification parameters of Prime 150kVA series diesel generator set			
Unit model:SO-120KW		Steady state voltage adjustment(%): ≤±0.5	
Rated power:120KW/Prime power: 138KW		Voltage fluctuation rate (%):≤±0.5	
Rated power factor: COSΦ=0.8		Transient voltage adjustment rate (%): $+20{\sim}-15$	
Rated output voltage:220V/380V		Load abrupt voltage stability time (s):≤2	
Rated current:216A		Steady state frequency adjustment rate (%):≤±1	
Rated frequency:50Hz		Frequency wave rate (%):≤±2	
Rated speed:1500rpm		Transient frequency adjustment rate (%): $\pm 10{\sim} -7$	
Start mode: Electric		Load mutation frequency stabilization time (S):≤2	
Size:2470*930*1450(LxWxH mm)		Unit weight:1550kg	
Prime 150Kva diesel generator configuration			
	Model		WP6D132E200
Diesel engine	Rated power		120KW
	Cylinders		6
	Bore * stroke (mm)		105*130mm
	Туре		Straight line, water cooling, four stroke
	Intake mode		Turbo charged
	Combustion mode		Direct injection combustor
	Displacement (L)		6.75L
	Fuel consumption rate (g/kw.h)		≤198g/kw.h
	Cooling mode		Closed water cooling
	Startup mode		24V DC electric start
	Lubrication method		Pressure and splash lubrication
Alternator	Model		STF-120
	Rated power		120KW
	Rated current		216A
	Rated voltage		220/380V
	Frequency		50HZ
	Speed		1500rpm
	Power factor		0.8
	Phase number		Three phase four wire
	Туре		Pure copper brushless
	Protection grade		IP22