Roundfin

RD-2
RD-B
MORTUARY FREEZER

ROUNDFIN is committed to serving funeral industry. Provide accurate temperature control and convenient overall device for global funeral sector.

INTRODUCTION:

ROUNDFIN focus on all-in-one funeral refrigerator which can effectively ensure temperature stability and product robustness. There are differences of 1 body to 9 bodies according to the use scene.
Each room is equipped with single door& separate refrigeration compressor & separate switch which more effectively ensures the accurate temperature and save electricity.

FEATURE:

1: The whole body is made of 304 stainless steel material.
Anti corrosion and anti rust. It is all-in-one machine without installation on-site.
2: Disposable 10 cm foam machine overall. Make cold room quickly reach the specified temperature.
3: LED display. Standard temperature: from 0℃ to -10℃. Adjustable from -15℃ to 5℃ .
4: Separate compressor system and temperature controller system Original SECOP compressor, service life: 8-10 years.
5: Body tray is made of 304 stainless steel.
Capacity: 200kg, anti drop design with double rows of nylon silent rollers.
Common size with Roundfin lifting trolley's tray.
6: Seven types of fault alarms: high temperature/low temperature/long time door opening/ low voltage/sensor failure/power failure/low battery.
7: Each room with door locks and spare keys to ensure the safety and privacy.
8: 5 inch universal wheel for easy move.



• INSULATION TECHNOLOGY

10 cm foamed in place urethane
It is a green/ environmental foam material.
Disposable foam machine overall.

• COOLING QUALITY

High quality compressor (Germany Secop Compressor is optional) to be sure the necessary temperature.

• SAFETY DOOR

Safe door locked system, with lock keys. Unique door seal design for the minimum loss of cold temperature during a door opening. Door seal belt can be replaced. Door frame with a unique one-piece design.



• REMOVABLE TRAY

Separate body tray with the strong sliding system to make sure easy to pull out and pull back.Note: All the body trays (mortuary refrigerator, lifting cart, walk- in rack) size is the same.

• ALARM FUNCTION

Seven types of fault alarms: high temperature /low temperature/long time door opening/ low voltage/sensor failure/power failure/ low battery.

• UNIVERSAL WHEEL

5 inch universal wheel for easy move.14pcs maintenance free nylon roller (7pcs of each side) for easy move the body tray.

SPECIFICATION LIST:

Model No.	RD-2
Material	Stainless steel 304 (201/316optional)
Thickness of stainless steel	Outer:1.0 Body Tray:1.0 Inner:0.6
Compressor Place	Back of the freezer
External Size(mm)	2280*860*1275
Inner Room Size(mm)	1950*630*440
Body Tray size(mm)	1940*580
Body Tray	2
Body Tray load capacity	200kg
Compressor	Germany Secop/Chinese compressor(optional)
Compressor Number	2 independent control of each chamber
Refrigerant	R404A
Temperature	Standard:0 to -10℃(optional -15 to 5℃)
Temperature Accuracy	1℃
Working temperature	10-38℃
Foamed urethane thickness(mm)	100
Chamber Height(mm)	440
Door	2
Rate of work	436W/1.2A
Voltage	220V/50HZ(110V/60HZ) optional
Weight	280kg
Packing Size(mm)	2400*960*1375
CBM	3.2
Package	Plywood
Certification	CE
Customization	All can be

Model No.	RD-B
Material	Stainless steel 304 (201/316optional)
Thickness of stainless steel	Outer:1.0 Body Tray:1.0 Inner:0.6
Compressor Place	Top of the freezer
External Size(mm)	2060*800*1475
Inner Room Size(mm)	1950*630*440
Body Tray size(mm)	1940*580
Body Tray	2
Body Tray load capacity	200kg
Compressor	Germany Secop/Chinese compressor(optional)
Compressor Number	2 independent control of each chamber
Refrigerant	R404A
Temperature	Standard:0 to -10℃(optional -15 to 5℃)
Temperature Accuracy	1℃
Working temperature	10-38℃
Foamed urethane thickness(mm)	100
Chamber Height(mm)	440
Door	2
Rate of work	436W/1.2A
Voltage	220V/50HZ(110V/60HZ) optional
Weight	280kg
Packing Size(mm)	2140*840*1575
CBM	2.9
Package	Plywood
Certification	CE
Customization	All can be

USAGE SCENARIO: