

ROUNDFIN is committed to serving funeral industry. Provide accurate temperature control and convenient overall device for global funeral sector.

INTRODUCTION:

ROUNDFIN focus on all-in-one funeral refrigerator which can effectively ensure temperature stability and product robustness. There are differences of 1 body to 9 bodies according to the use scene. Each room is equipped with single door& separate refrigeration compressor & separate switch which more effectively ensures the accurate temperature and save electricity.

FEATURE:

1: The whole body is made of 304 stainless steel material.

Anti corrosion and anti rust. It is all-in-one machine without installation on-site. 2: Disposable 10 cm foam machine overall. Make cold room quickly reach the specified temperature.

- 3: LED display. Standard temperature: from 0°C to -10°C. Adjustable from -15°C to 5°C.
- 4: Separate compressor system and temperature controller system Original SECOP compressor, service life: 8-10 years.
- 5: Body tray is made of 304 stainless steel.

Capacity: 200kg, anti drop design with double rows of nylon silent rollers. Common size with Roundfin lifting trolley's tray.

- 6: Seven types of fault alarms: high temperature/low temperature/long time door opening/ low voltage/sensor failure/power failure/low battery.
- 7: Each room with door locks and spare keys to ensure the safety and privacy. 8: 5 inch universal wheel for easy move.



INSULATION TECHNOLOGY

10 cm foamed in place urethane It is a green/ environmental foam material. Disposable foam machine overall.



COOLING QUALITY

High quality compressor (Germany Secop Compressor is optional) to be sure the necessary temperature.



SAFETY DOOR

Safe door locked system, with lock keys. Unique door seal design for the minimum loss of cold temperature during a door opening. Door seal belt can be replaced. Door frame with a unique one-piece design.



REMOVABLE TRAY

Separate body tray with the strong sliding system to make sure easy to pull out and pull back. Note: All the body trays (mortuary refrigerator, lifting cart, walk- in rack) size is the same.



ALARM FUNCTION

Seven types of fault alarms: high temperature /low temperature/long time door opening/ low voltage/sensor failure/power failure/ low battery.



UNIVERSAL WHEEL

5 inch universal wheel for easy move.14pcs maintenance free nylon roller (7pcs of each side) for easy move the body tray.





SPECIFICATION LIST:

Model No.	RD-
Material	Stainless steel 304 (201/316optiona
Thickness of stainless steel	Outer:1.0 Body Tray:1.0 Inner:0
Compressor Place	Back of the freez
External Size(mm)	2280*1640*210
Inner Room Size(mm)	1950*630*44
Body Tray size(mm)	1940*58
Body Tray	
Body Tray load capacity	200k
Compressor	Germany Secop/Chinese compressor(optional
Compressor Number	8 independent control of each chamb
Refrigerant	R404
Temperature	Standard:0 to -10°C(optional -15 to 5°C
Temperature Accuracy	1
Working temperature	10-38
Foamed urethane thickness(mm	10
Chamber Height(mm)	44
Door	
Rate of work	1744W/1.2
Voltage	220V/50HZ(110V/60HZ) option
Weight	880k
Packing Size(mm)	2400*1750*220
CBM	9
Package	Plywoo
Certification	
Customization	All can b
USAGE SCENARIO:	

Model No.	RD-
Material	Stainless steel 304 (201/316optiona
Thickness of stainless steel	Outer:1.0 Body Tray:1.0 Inner:0.
Compressor Place	Back of the freeze
External Size(mm)	2280*2360*178
Inner Room Size(mm)	1950*630*44
Body Tray size(mm)	1940*58
Body Tray	
Body Tray load capacity	200k
Compressor	Germany Secop/Chinese compressor(optional
Compressor Number	9 independent control of each chambe
Refrigerant	R404
Temperature	Standard:0 to -10℃(optional -15 to 5℃
Temperature Accuracy	1°
Working temperature	10-38°
Foamed urethane thickness(mi	n) 10
Chamber Height(mm)	44
Door	
Rate of work	1962W/1.2
Voltage	220V/50HZ(110V/60HZ) option
Weight	1000k
Packing Size(mm)	2320*2440*190
CBM	10.
Package	Plywoo
Certification	
Customization	All can b

TOMUL OULIMIIIO.







Page 015 Page 016