

# -86°C Freezer



## Technical Parameters

Model	BDF-86V50	BDF-86V158	BDF-86V348
Capacity	50L	168L	348L
Shelf	2 pcs, S.S.		3 pcs, S.S.
Refrigeration Type	Direct refrigeration		
Defrosting Type	Manual		
Refrigerant/g	R600a, 85g; R290, 15g; R1150, 27g; R14, 20g	Mixed refrigerant, CFC free	
Noise	55dB(A)	53dB(A)	55dB(A)
Ambient Temp.	10~32°C		
Temp. Range	-40°C~-86°C		
Evaporator	Built-in coil, copper pipe		
Condenser	Copper tube and aluminum fin		
Sensor	PT1000	PTC	
Thermostat	Electronic thermostat		
Display	LED		
Power Supply	110~220V/50~60Hz		
Power	529W	650W	810W
Current	3.7A	4.6A	5.9A
Internal Material	S.S. 304		
External Material	Sprayed cold-rolled steel plate		
Lagging	Foamed polyurethane cyclopentane		
Audible and Visual Alarm	High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door switch alarm		
Net Weight	92kg	196kg	264kg
Gross Weight	134kg	253kg	332kg
Internal Size(W*D*H)	360×456×395mm	465×455×820mm	490×612×1150mm
External Size(W*D*H)	660×715×1165mm	844×807×1594mm	869×989×1924mm
Package Size(W*D*H)	765×825×1350mm	1000×970×1790mm	1020×1180×2130mm