

Orbital Shaker



Features:

- * Electronic adjustment of speed and timer.
- * Double LEDs for independent display of time and speed.
- * Speed range of 40~200rpm.
- * Fixed board face, max. load capacity is 2kg with platform.
- * Continuous operation(endless).
- * Electronic time switching clock: 1min~19h59min.

 * Multifunctional model supports various accessories and has a wide range of applications.

Technical Parameters: DIODASE.CC / WWW.DIODASE.COM

Model	SK-O180-S	
Туре	Basic model	Multifunctional model
Item No.	8072210201	8072210300
Speed Range	40~200rpm	
Work Plate Dimension(W*D)	268*268mm	
Orbital Diameter	20mm	
Max. Load Capacity(With Platform)	2kg	
Display	LED	
Time Setting Range	1min~19h59min	
Motor Type	DC motor	
Protection Class	IP21	
Standard Accessory	Fixed tray	Universal attachment with 3 bars(18900025)
Consumption	20W	
Motor Input Consumption	20W	
Motor Output Consumption	16W	
Power Supply	AC100~240V, 50/60Hz	
External Size(W*D*H)	294*348*123mm	
Net Weight	3.1kg	
Packing Size(W*D*H)	425*360*205mm	
Gross Weight	3.9kg	

E-mail: export@biobase.com