



Ducted Fume Hood



LED Display
Digital LED display:
Airflow Level



Waterproof Socket



Universal Wheel



Water Remote Control



Water Tap



Water Tap & Water Sink

ADVANTAGE

1. Adjustable air speed: 9 levels.
2. Microprocessor control system, LED display.
3. Resistant to moderate acid and alkali.
4. With memory function in case of power-failure.
5. Manual front glass window, height adjustable.
6. Built-in PP centrifugal blower; low noise, easy installation.

TECHNICAL PARAMETERS

Model		FH1000(E)	FH1200(E)	FH1500(E)	FH1800(E)
External Size(W*D*H)		1000*800*2515mm	1200*800*2515mm	1500*800*2515mm	1800*800*2515mm
Internal Size(W*D*H)		790*600*870mm	990 *600*870mm	1290*600*870mm	1590*600*870mm
Work Surface Height		900mm			
Max Opening		750mm			
Air Velocity		0.3~0.8m/s			
System Exhaust Volume		570 m³/h	710 m³/h	930 m³/h	1140 m³/h
Noise		≤68dB			
Exhaust Duct		PVC,Standard length; 5 meters,Φ300mm			
Pipe Strap		2 pcs			
LED Lamp		20W *1		40W *1	
Blower		Built-in PP centrifugal blower			
Front Window		Manual, 5mm toughened glass, height adjustable			
Power Supply		220V±10%, 60/50Hz; 110V±10%, 60Hz			
Consumption		400W	400W	500W	500W
Material	Exterior	1.0mm cold-rolled steel with anti-bacterial powder coating			
	Interior	Compact laminate board with good acid and alkali resistance function			
	Work table	Chemical resistant phenolic resin			
Standard Accessory		PP Water sink, Total load of 2 waterproof sockets: 500w, Base cabinet, Water tap, 5 meters Exhaust duct(φ300mm).			
Optional Accessory		Gas valve, gas tap			
Gross Weight		186kg; 81kg	207kg; 89kg	233kg; 101kg	279kg; 130kg
Package	Main Body	1145*960*1865mm	1345*960*1865mm	1645*960*1875mm	1945*960*1875mm
	Base Cabinet	1145*960*1040mm	1345*960*1040mm	1645*960*1060mm	1945*960*1040mm