



Ducted Fume Hood



LED Display



Waterproof Socket



Water&Gas Remote Control



Double Layer
1.2mm sheet metal surface,
melamine board inward.

ADVANTAGE

1. UV lamp for sterilization.
2. resistant to weak acid and alkali.
3. Adjustable air speed: 9 levels.
4. Motorized front window, height adjustable.
5. Microprocessor control system, LED display.
6. With memory function in case of power-failure.

TECHNICAL PARAMETERS

Model	FH1000(A)		FH1200(A)		FH1500(A)		FH1800(A)		
External Size (W*D*H)	1040*800*2200mm		1240*800*2200mm		1540*800*2200mm		1840*800*2200mm		
Internal Size (W*D*H)	820*670*730mm		1020*670*730mm		1320*670*730mm		1620*670*730mm		
Work Surface Height	850mm								
Max Opening	520mm								
Air Velocity	0.3~0.8m/s								
Exhaust Air Volume	590m³/h		730m³/h		950m³/h		1170m³/h		
Noise	≤68dB								
Exhaust Duct	PVC, Standard length: 5 meters. Φ300mm								
LED Lamp	8W*1		12W*1		16W*1		16W*1		
UV Lamp	Emission of 253.7 nanometers for most efficient decontamination								
Blower	Built-in centrifugal blower; Speed adjustable								
Front Window	5mm toughened glass; Motorized; Height adjustable								
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz								
Consumption	400W		400W		500W		500W		
Material	Exterior	Cold-rolled steel with anti-bacteria powder coating.							
	Interior	Compact laminate board with good acid and alkali resistance function							
	Work Table	Chemical resistant phenolic resin							
Standard Accessories	UV lamp*2, LED lamp, Water tap, Gas tap, Water sink, Base cabinet								
	Total load of 2 waterproof sockets: 500W								
	5 meters PVC exhaust duct, pipe strap*2								
Optional Accessory	Active carbon filter, HEPA filter								
Gross Weight	286kg		317kg		350kg		400kg		
Package	Main Body	1190*990*1690mm		1390*990*1690mm		1690*990*1690mm		1990*990*1690mm	
	Base Cabinet	1190*990*900mm		1390*990*900mm		1690*990*900mm		1990*990*900mm	