

Table Top Shaker



Features:

- * Intelligent sound and light alarm microprocessor controller.
- * LCD display shows the set parameters and measured parameters, easy to operate.
- * Running parameter memory function to avoid tedious operation.
- * Microcomputer control brushless DC motor accurately.
- * Power off recovery function, automatically restore operation according to the original setting program.


Technical Parameters:

Model	BJPX-SZ10			
Oscillation Mode	Rotary shaking			
Speed Range	30~300rpm			
Speed Accuracy	±1rpm			
Amplitude	26mm			
Display	LCD Display			
Timing Range	0~9999min/hour			
Tray Size	680*500mm			
Tray Number	1pc			
Flask Clamp	Default Capacity: 250ml*24 Standard Capacity: 24*250ml/18*500ml/14*1000ml/ 7*2000ml(Choose one of them) Max Capacity: 35*250ml/24*500ml/20*1000ml/12*2000ml			
Drive Mode	Single axis balanced drive type			
Curve Programming	Fixed value control speed			
Ambient Temp.	15~35℃			
Consumption	80W			
Power Supply	AC100~240V, 50/60Hz			
External Size(W*D*H)	570*680*290mm			
Net Weight	79kg			
Package Size(W*D*H)	700*760*470mm			
Gross Weight	101kg			

Table Top Shaker

Feature:

- * Intelligent sound and light alarm, microprocessor controller.
- * The LCD display shows the set parameters and the measured parameters, which is easy to operate.
- * Running parameter memory function to avoid tedious operation.
- * DC brushless motor design, long service life and maintenance-free.



* The acceleration control circuit ensures that the oscillator starts slowly, accelerates smoothly, and ensures the safety of the experimental samples.



Technical Parameters:

Model	BJPX-SZ11		
Oscillation Mode	Rotatory shaking		
Speed Range	30~300rpm		
Speed Accuracy	±1rpm		
Amplitude	50mm		
Display	LCD Display		
Timing Range	0~9999min/hour		
Tray Size	680*500mm		
Tray Number	1pc - evnort@hinhage com		
Flask Clamp	Default Capacity: 250ml*24 Standard Capacity: 24*250ml/18*500ml/14*1000ml/ 7*2000ml(Choose one of them) Max Capacity: 35*250ml/24*500ml/20*1000ml/12*2000ml		
Drive Mode	Single axis balanced drive type		
Curve Programming	Fixed value control speed		
Ambient Temp.	15~35℃		
Consumption	80W		
Power Supply	AC100~240V, 50/60Hz		
1 Owel Oupply	710 100 2101, 00/00/12		
External Size(W*D*H)	680*570*300mm		
	Section of the sectio		
External Size(W*D*H)	680*570*300mm		

Optional Clamp:

Model		BJPX-SZ11	
	100ml	48	
	250ml	35	
Triangular beaker	500ml	24	
Max. capacity (pcs)	1000ml	20	
	2000ml	12	
	3000ml	8	
Tube Rack (pcs)		4	
96-well Plates		18	
Clip-type Shaking Plate		2	

Note: This table is the maximum optional capacity, please choose according to your requirement.

105