

Table Top Shaker



Features:

- * The LCD display shows all the set parameters and actual measured parameters, and the operation is very simple.
- * DC brushless motors have a long service life and require no maintenance.
- * With the power-off recovery function, the equipment can automatically resume operation according to the original set program.
- * Equipped with an intelligent sound and light alarm environment scanning microprocessor controller.
- * Parameter memory function, avoiding cumbersome operations.

Technical Parameters:

Model	BJPX-SY10	BJPX-SY11
Oscillation Mode	Rotary shaking	
Speed Range	20~300rpm	
Speed Accuracy	±1rpm	
Amplitude	26mm	50mm
Display	LCD display	
Timing Range	0~9999min/hour	
Tray Size	900*600mm	
Flask Clamp	500ml*24(Default)/250ml*35/1000ml*18/2000ml*12/3000ml*6/5000ml*6	
Drive Mode	Single axis balanced drive type	
Curve Programming	Fixed value control speed	
Ambient Temp.	15~35℃	
Consumption	150W	
Power Supply	AC220V, 50/60Hz	
External Size(L*W*H)	910*665*460mm	
Net Weight	130kg	
Packing Size(L*W*H)	1009*724*562mm	
Gross Weight	155kg	

Optional Clamp:

Model		BJPX-SY10	BJPX-SY11
Triangular Beaker Max. Capacity(pcs)	250ml	54	
	500ml	40	
	1000ml	24	
	2000ml	15	
	3000ml	6	
	5000ml	6	
Tube Rack(pcs)		5	
96-well Plate		36	
Clip-type Shaking Plate		2	

BIOBASE

E-mail: export@biobase.com

www.biobase.cc / www.biobase.com