

Ductless PP Fume Hood



FEATURES

1. The case is made of 8mmPP plate, with good finish and corrosion resistance.
2. The front window has 8°physiological incline, ergonomic design, larger viewing angle.
3. The front window is foldable acrylic window, and the lower acrylic window has the function of stopping at will.
4. Electronic control system with anti-overload, anti-shock and other functions, stable performance, long service life.
5. With power failure memory function, that is, when encountering a sudden power failure, power again can maintain the working state before the power failure, convenient experimental operation.

TECHNICAL PARAMETERS

Model	FH700(PD)
External Size	700*700*1100mm
Internal Size	680*606*688mm
Max Opening	640mm
Airflow Volume	230 m ³ /h
Air Velocity	0.3~0.8m/s
Noise	≤65dB(A)
LED Lamp	15W
Illumination	≥400lx
Blower	Built-in centrifugal blower
Power Supply	220V, 50/60Hz
Consumption	150W
Material	Main Body: PP plate, thickness 8mm Work Table: Chemical resistant phenolic resin
Standard Accessory	Active carbon filter*2
Optional Accessory	Water tap, Gas tap, Water sink, Base stand, UV lamp, HEPA filter
Net Weight	67kg
Gross Weight	87kg
Package Size	820*820*1280mm

Ductless PP Fume Hood



FEATURES

1. The case is made of 8mmPP plate, with good finish and corrosion resistance.
2. The front window has 8°physiological incline, ergonomic design, larger viewing angle.
3. The front window is foldable acrylic window, and the lower acrylic window has the function of stopping at will.
4. Electronic control system with anti-overload, anti-shock and other functions, stable performance, long service life.
5. With power failure memory function, that is, when encountering a sudden power failure, power again can maintain the working state before the power failure, convenient experimental operation.

TECHNICAL PARAMETERS

Model	FH1000(PD)	FH1500(PD)
External Size	1000*700*1100mm	1500*700*1100mm
Internal Size	980*606*688mm	1480*606*688mm
Max Opening	640mm	
Airflow Volume	230 m ³ /h	460 m ³ /h
Air Velocity	0.3~0.8m/s	
Noise	≤65dB(A)	
LED Lamp	15W	15W*2
Illumination	≥400lx	
Blower	Built-in centrifugal blower	Built-in centrifugal blower*2
Power Supply	220V, 50/60Hz	
Consumption	150W	300W
Material	Main Body: PP plate, thickness 8mm Work Table: Chemical resistant phenolic resin	
Standard Accessory	Active carbon filter*2	Active carbon filter*4
Optional Accessory	Water tap, Gas tap, Water sink, Base stand, UV lamp, HEPA filter	
Package Size	1120*820*1280mm	1630*830*1330mm
Net Weight	85kg	120kg
Gross Weight	115kg	150kg