

Ductless PP Fume Hood



FEATURES

- 1. The case is made of 8mmPP plate, with good finish and corrosion resistance.
- 2. The front window has 8°physiological incline, ergonomic design, larger viewing angle.
- 3. The front window is foldable acrylic window, and the lower acrylic window has the function of stopping at will.
- 4. Electronic control system with anti-overload, anti-shock and other functions, stable performance, long service life.
- 5. With power failure memory function, that is, when encountering a sudden power failure, power again can maintain the working state before the power failure, convenient experimental operation.

TECHNICAL PARAMETERS

Model	FH700(PD)
External Size	700*700*1100mm
Internal Size	680*606*688mm
Max Opening	640mm
Airflow Volume	230 m³/h
Air Velocity	0.3~0.8m/s
Noise	≤65dB(A)
LED Lamp	15W
Illumination	≥400lx
Blower	Built-in centrifugal blower
Power Supply	220V, 50/60Hz
Consumption	150W
Material	Main Body: PP plate, thickness 8mm Work Table: Chemical resistant phenolic resin
Standard Accessory	Active carbon filter*2
Optional Accessory	Water tap, Gas tap, Water sink, Base stand, UV lamp, HEPA filter
Net Weight	67kg
Gross Weight	87kg
Package Size	830*830*1330mm

Ductless PP Fume Hood



FEATURES

- 1. The case is made of 8mmPP plate, with good finish and corrosion resistance.
- 2. The front window has 8°physiological incline, ergonomic design, larger viewing angle.
- 3. The front window is foldable acrylic window, and the lower acrylic window has the function of stopping at will.
- 4. Electronic control system with anti-overload, anti-shock and other functions, stable performance, long service life.
- 5. With power failure memory function, that is, when encountering a sudden power failure, power again can maintain the working state before the power failure, convenient experimental operation.

TECHNICAL PARAMETERS

Model	FH1000(PD)	FH1500(PD)
External Size	1000*700*1100mm	1500*700*1100mm
Internal Size	980*606*688mm	1480*606*688mm
Max Opening	640mm	
Airflow Volume	230 m³/h	460 m³/h
Air Velocity	0.3~0.8m/s	
Noise	≤65dB(A)	
LED Lamp	15W	15W*2
Illumination	≥400lx	
Blower	Built-in centrifugal blower	Built-in centrifugal blower*2
Power Supply	220V, 50/60Hz	
Consumption	150W	300W
Material	Main Body: PP plate, thickness 8mm Work Table: Chemical resistant phenolic resin	
Standard Accessory	Active carbon filter*2	Active carbon filter*4
Optional Accessory	Water tap, Gas tap, Water sink, Base stand, UV lamp, HEPA filter	
Package Size	1130*830*1330mm	1630*830*1330mm
Net Weight	85kg	120kg
Gross Weight	115kg	150kg