

Constant-Temperature Incubator

Features:

- * Microcomputer-based smart temperature controller.
- * LCD display for setting temperature and the temperature in the chamber, parameter memory and recovery function for the purpose of protection against power failure, computer system halt and data loss; protection and alarming against excessive temperature, failure of sensors, creep and , over-current; sound & light alarming; timing function.
- * Separate temperature limiting and alarming system, automatic suspension in time of exceeding temperature limit (optional).
- * UV sterilizing system (optional).
- * RS-485 portal, capable of being connected with printer or computer, recording variations of temperature parameters (optional).
- * Double door (optional).



Technical Parameters:

Model	BJPX-H50IV	BJPX-H80IV	BJPX-H160IV	BJPX-H270IV
Capacity	50L	80L	160L	270L
Temp. Range	RT+5~65°C			
Temp. Resolution	0.1			
Temp. Fluctuation	±0.5°C			
Temp. Uniformity	±1°C(37°C)			
Time Range	1~9999mins			
Shelves(Standard)	2pcs			
Consumption	250W	300W	400W	600W
Power Supply	AC220V±10%, 50/60Hz(Standard) AC110±10%, 60Hz(Optional)			
Internal Size(mm)	350*360*410	400*400*500	500*500*650	600*600*750
External Size(mm)	450*520*680	500*560*760	600*620*910	720*690*1020
Packing Size (mm)	550*620*780	600*660*860	700*720*1010	820*790*1120
Gross Weight (kg)	40	47	70	90

Constant-Temperature Incubator

Features:

- * Large LED display, multiple groups of data to be displayed at a time; function of timing and over-temperature protection.
- * Two-layer toughened-glass observation window.



Website: www.biobase.cc / www.meihuatrade.com

Technical Parameters:

Model	BJPX-H30II	BJPX-H48II	BJPX-H64II	BJPX-H123II	BJPX-H230II
Capacity	30L	45L	65L	125L	230L
Temp. Range	RT+5~80°C				
Temp. Fluctuation	±0.2°C				
Time Setting	1~9999mins				
Shelves	2 pcs/adjustable				
Consumption	150W	250W	500W	600W	700W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)				
Internal Size(mm)	310*310*310	350*350*350	400*360*450	500*450*550	600*500*750
External Size(mm)	460*510*695	500*550*735	550*550*840	636*680*915	730*670*1220
Package Size(mm)	550*570*765	620*585*800	640*640*905	730*720*1000	900*800*1350
Gross Weight(kg)	51	56	62	71	105