

## BM-50 Series Rapid Moisture Meter

### Features:

- \* LCD Display
- \* RS232 communication interface
- \* Convenient and quick operating with 6 buttons.
- \* Heating element, Halogen lamps, proper for samples requires quick heating.
- \* Adopting heating-insulated weighing sensor avoids accuracy affected by heating.



### Technical Parameters:

Model	BM-50-10	BM-50-5	BM-50-1
Capacity	50g		
Weight Readability	0.01g	0.005g	0.001g
Repeatability Standard Deviation	0.01g	0.05g	0.002g
Linear Error	0.01g	0.05g	0.002g
Moisture Percentage Accuracy	0.3%	0.2%	0.1%
Scale Size	Φ90mm		
Temperature Capacity	50~180°C	50~180°C	50~180°C
Ambient Temperature	10~30°C	10~30°C	10~30°C
Power Supply	AC110/220V±10%, 50/60Hz; Power cord, no battery		
Package Size	370*470*350mm		
Gross Weight	4.1kg		

## Electronic Density (Specific Gravity) Balance



### Technical Parameters:

Model	BA-100D	BA-200D
Max Capacity	100g	200g
Repeatability	10mg	
Linear Error	20mg	
Min Capacity	10mg	
Fixed Support	H=203mm	
Scale Size	Φ110mm	
Output	RS-232C	
Power Supply	AC110/220V±10%, 50/60Hz; Power cord, no battery	
Gross Weight	3.2kg	
Package Size	377*281*278mm	
Accessories	Measuring platform, measuring cup, fixed support, thermometer, doublehook weights, platinum wire, plumb bob, wire basket, balance body, adaptor and standard weights	

## Microscope

### Microcirculation Microscope

#### Application:

Microcirculation microscope is used the early diagnosis, guide treatment and observation for varies diseases including cardiovascular, diabetes, hypertension, stroke, rheumatoid arthritis, etc.It is widely used in medicine, health care products, human health consulting, beauty care and other fields. It is also used for individual microcirculation monitoring



### Technical Parameters:

Model	WXH-8	WXH-10	WXH-12
Magnification	380X	480X	580X
Display Size(mm)	161*121	204*153	185*240
Objective	10X		
Focus System	Coaxial coarse/ Slightly adjusted, Z axis movement, Mechanical upper and lower limits		
Stage	360°revolve, X,Y axis movement ,moving range 30*80mm		
Illumination	LED illumination with high brightness and lower consumption, new luminaire with lower temperature and 10,000-200,000h working life, 90°revolve left and right		
Power Supply	12V		
Camera	Color camera system, HD LCD display		
Standard Accessory	Aluminum box, Display screen, Power cable, Asphalt, Manual, Flip chart, Microcirculation flattery		
Package Size	270*340*380mm	300*380*380mm	
Gross Weight	5.5kg	7kg	