

Table Top Shaker



Features:

- * Ultra-low speed start function, the start speed is adjustable.
- * Restore function after power on.
- * Equipped with high-quality servo motor, the control speed is accurate, the high and low speed performance is good, and the stability is strong.
- * The speed-up control circuit is adopted to start slowly and accelerate steadily to ensure the safety of experimental samples.
- * Open-type oscillation equipment, used for centralized temperature control within the same controlled greenhouse.

Technical Parameters:

Model	SK-852	SK-872	SK-882F
Oscillation Mode	Rotatory shaking		Reciprocating shaking
Speed Range	20~300rpm	20~300rpm	20~260rpm
Speed Accuracy	±1rpm		
Amplitude	Φ50mm	Φ26mm	0-50mm
Controller	PID		
Display	LCD		
Timing Range	0~9999h/min		
Circulation Mode	Natural convection		
Drive Mode	Multi-dimensional drive		
Tray Size	800*600mm	950*730mm	800*600mm
Tray Quantity	2pcs		
Standard Capacity (Flask Clamps Qty)	250ml*46&1000ml*18	250ml*71&1000ml*30	250ml*46&1000ml*18
Optional Flask Clamps	100ml*132 or 250ml*96 or 500ml*66 or 1000ml*40	250ml*160 or 500ml*106 or 1000ml*60 or 2000ml*40 or 3000ml*24	250ml*96 or 500ml*66 or 1000ml*40 or 100ml*132
Optional Sticky Board	250ml*96 or 500ml*64 or 1000ml*40	250ml*142 or 500ml*106 or 1000ml*60 or 2000ml*40 or 3000ml*24	250ml*96 or 500ml*64 or 1000ml*40
External Material	Cold-rolled steel with anti-bacterial powder coating		
Consumption	200W	300W	200W
Power Supply	220V±10%, 50/60Hz(Standard); 110V±10%, 60Hz(Optional)		
External Size(W*D*H)	900*650*900mm	1040*760*1050mm	900*650*900mm
Net Weight	250kg	380kg	280kg
Packing Size(W*D*H)	1110*800*1155mm		
Gross Weight	270kg	420kg	300kg