

Pipettes

Micro Pipette(Disinfection of Half)



Application:

Mechanical Pipette is suitable for pharmaceutical R&D centers, school laboratories, pharmaceutical and chemical R&D companies, chemical synthesis and other places.

Features:

- * Light weight and ergonomic design to ensure a better sense of use.
- * Digital display, easy to read data.
- * The pipettes cover volume range of 0.5µl to 1ml.
- * Easy to calibrate and maintain.
- * The low part can be autoclaved without affecting performance and comfort.
- * Manufactured from innovative materials.

Technical Parameters:

Volume	Increment	Test Volume(µl)	Capacity Tolerance(%)	Test Repeatability(%)
0.5-10µl	0.1µl	1	±2	≤3
		5	±1.5	≤2
		10	±1	≤2
2-20µl	0.1µl	2	±2	≤3
		10	±1.5	≤2
		20	±1	≤2
10-100µl	1µl	10	±2	≤2
		50	±1.5	≤1
		100	±1	≤1
20-200µl	1µl	20	±2	≤2
		100	±1.5	≤1
		200	±1	≤1
100-1000µl	5µl	100	±2	≤1
		500	±1	≤0.5
		1000	±1	≤0.5

Micro Pipette(Disinfection of the Whole)



Application:

Micro Pipette is suitable for pharmaceutical R&D centers, school laboratories, pharmaceutical and chemical R&D companies, chemical synthesis and other places. It is often used in the laboratory to pipette a small amount of liquid or a small amount of liquid. The specifications are different, and the pipette tips of different specifications are matched with different sizes of pipette tips.

Features:

- * The pipettes are autoclavable in their entirety without compromising performance or comfort.
- * Light weight and ergonomic design to ensure a better sense of use.
- * The pipettes cover volume range of 0.5µl to 1ml.
- * The interior of the product has good air tightness, stable and accurate, and no liquid leakage.
- * Easy to calibrate and maintain.
- * Digital display, easy to read data.

Technical Parameters:

Volume	Increment	Test Volume(µl)	Capacity Tolerance(%)	Test Repeatability(%)
0.5-10µl	0.1µl	1	±12	≤6
		5	±8	≤4
		10	±8	≤4
2-20µl	0.1µl	2	±12	≤6
		10	±8	≤4
		20	±4	≤2
10-100µl	1µl	10	±8	≤4
		50	±3	≤1.5
		100	±2	≤1
20-200µl	1µl	20	±4	≤2
		100	±2	≤1
		200	±1.5	≤1
100-1000µl	5µl	100	±2	≤1
		500	±1	≤0.5
		1000	±1	≤0.5