

Ultrasonic Cleaner



Introduction:

Ultrasonic cleaner is a non-polluting, non-damaging, multi-purpose cleaning equipment. It not only has a powerful cleaning effect on objects with complex shapes, but also accelerates dissolution and emulsification. Ultrasonic cleaner has the unparalleled advantages of other physical cleaning or chemical cleaning, and is widely used in service industry, electronics industry, pharmaceutical industry, laboratory, machinery industry, cemented carbide industry, chemical industry and other fields.

Features:

- * Standard accessories: 1pc of soundproof cover, 1pc of basket, 1pc of PVC pipe.
- * The shell and inner cavity are made of 304 stainless steel, which is anti-corrosion.
- * LED display for UC-VAD series.

Technical Parameters:

Model	UC-18VAD	UC-24VAD	UC-36VAD	UC-48VAD	UC-60VAD
Capacity(L)	6.5	10	15	22.5	30
Ultrasonic Frequency	Double Frequency, 28/40kHz				
Time Range/ Heating Temperature	1-99min/RT~80℃				
Ultrasonic Power	180W	240W	360W	480W	600W
Heating Power	500W				
Power Supply	220V 50Hz				
Tank Size(mm)	300*150*150	300*240*150	330*300*150	500*300*150	500*300*200
External Size(mm)	330*180*310	330*270*310	360*330*310	530*330*310	530*330*350
Packing Size(mm)	440*280*355	440*360*355	475*415*380	640*415*380	640*415*425
Gross Weight(kg)	7	9	11	14	17

* Remark: VAD is based on the digital D model and adds another frequency of 28khz.



Introduction:

Ultrasonic cleaner is a non-polluting, non-damaging, multi-purpose cleaning equipment. It not only has a powerful cleaning effect on objects with complex shapes, but also accelerates dissolution and emulsification. Ultrasonic cleaner has the unparalleled advantages of other physical cleaning or chemical cleaning, and is widely used in service industry, electronics industry, pharmaceutical industry, laboratory, machinery industry, cemented carbide industry, chemical industry and other fields.

Features:

- * Standard accessories: 1pc of soundproof cover, 1pc of basket, 1pc of PVC pipe.
- * The shell and inner cavity are made of 304 stainless steel, which is anti-corrosion.
- * LED display for UC-AD series.

Technical Parameters:

Model	UC-18AD	UC-24AD	UC-36AD	UC-48AD	UC-60AD
Capacity(L)	6.5	10	15	22.5	30
Ultrasonic Frequency	Single Frequency, 40kHz				
Time Range/ Heating Temperature	1-99min/RT~80℃				
Ultrasonic Power	180W	240W	360W	480W	600W
Heating Power	500W				
Power Supply	220V 50Hz				
Tank Size(mm)	300*150*150	300*240*150	330*300*150	500*300*150	500*300*200
External Size(mm)	330*180*310	330*270*310	360*330*310	530*330*310	530*330*350
Packing Size(mm)	440*280*355	440*360*355	475*415*380	640*415*380	640*415*425
Gross Weight(kg)	7	9	11	14	17

* Remark: The AD model is a digital power adjustable model, which adds a power adjustable function based on the digital model(D model).