

Roller Mixer

Roller mixer is used for mixing blood samples, viscous substances and liquid-solid suspensions, prevention of blood coagulation and immune precipitation etc.



MX-T6-S



MX-T6-Pro

Features:

- * LCD display indicates the speed and time for MX-T6-Pro.
- * Speed range of 10-70rpm.
- * Six roller design for gentle rolling and easy to clean.

Technical Parameters:

Model	MX-T6-S	MX-T6-Pro
Item No.	8011312000	8011312100
Mixing Mode	Rocking & Rolling	
Speed Range	0~70 rpm	10~70 rpm
Rocking Amplitude	24mm	
Number of Roller	6 pcs	
Roller Length	280mm	
Max. Loading Weight	4kg	
Timing Range	/	1~1199min
Operation Mode	Continuous	Continuous or timing
Speed Display	Scale	LCD
Timer	/	Yes
Timer display	/	LCD
Motor Type	DC motor	
Ambient Temp.	5-40°C	
Relative Humidity	80%	
Protection Type	IP21	
Power Consumption	25W	30W
Power Supply	100~240V,50/60Hz	
External Size(W*D*H)	450*260*120mm	
Package Size(W*D*H)	595*390*245mm	
Gross Weight	5kg	5kg

Microplate Mixer



MX-M
With microplate clamp



MX-M
with universal top plate and
a tube adapter

Features:

- * A wide range of speed from 0 to 1500rpm.
- * Used for various mixing applications with optional adapters.
- * Maintenance-free brushless DC motor.
- * When the test tube adapter is selected, it must be matched with PS1.1.

Accessories:



Technical Parameters:

Model	MX-M
Item No.	8011202000
Shaking Mode	Orbital
Orbital Diameter	4.5mm
Max. Shaking Weight(with attachments)	0.5kg
Motor Type	DC brushless motor
Motor Input	18W
Motor Output	10W
Speed Range	0~1500rpm (single microplate) ; 0~1000rpm (double microplate)
Speed Display	Scale
Ambient Temp.	5~40°C
Relative Humidity	80%
Protection Type	IP21
Power Consumption	20W
Power Supply	100~240V,50/60Hz
Standard Accessories	18900042
External Size(W*D*H)	260*150*80mm
Package Size(W*D*H)	480*260*250mm
Gross Weight	3kg