

Roller Mixer

Roller mixer is used for mixing blood samples, viscous substances and liquid-solid suspensions, prevention of blood coagulation and immune precipitation etc.



MX-T6-S MX-T6-Pro

Features:

- * LCD display indicates the speed and time for MX-T6-Pro.
- * Speed range of 10-70rpm.
- * Six roller design for gentle rolling and easy to clean.

Technical Parameters:

Model	MX-T6-S	MX-T6-Pro
Item No.	8011312000	8031312100
Mixing Mode	Rocking & Rolling	. hishaaa aa
Speed Range	0~70 rpm	10~70 rpm
Rocking Amplitude	24mm	
Number of Roller	6 pcs	
Roller Length	280mm	
Max. Loading Weight	4kg	
Timing Range	1	1~1199min
Operation Mode	Continuous	Continuous or timing
Speed Display	Scale	LCD
Timer	1	Yes
Timer display	1	LCD
Motor Type	Brush DC motor	Brushless DC motor
Ambient Temp.	5-40°C	
Relative Humidity	80%RH	
Protection Type	IP21	
Power Consumption	25W	30W
Power Supply	AC100~240V,50/60Hz	
External Size(W*D*H)	450*250*100mm	
Package Size(W*D*H)	585*380*235mm	
Gross Weight	5kg	5kg



Introduction:

Roller mixer can be used for all kinds of common test tubes. It is especially suitable for mixing blood, viscous liquids and liquid-solid suspensions, prevention of blood coagulation and immune precipitation etc.

Features:

- * LCD display real-time indicates time and speed.
- * Time setting range of 1~99h59min.
- * Adjustable speed range of 20~100rpm, DC brushless motor, stable performance, low noise, maintenance free.
- * Gentle rolling process, continuous operation mode, safe and reliable.
- * Compatible with the different sizes of test tubes. Technical Parameters: Expont@blobase.com

Model	MX-T6-D	
Mixing Mode	Rocking & Rolling	
Speed Range	20~100rpm	
Rocking Amplitude	24	
Number of Roller	6	
Roller Length	280mm	
Roller Interval	5mm	
Max. Loading Weight	4kg	
Timing Range	1~99h59min	
Operation Mode	Timing or continuous	
Speed Display	LCD	
Timer	Yes	
Timer display	LCD	
Motor Type	DC brushless motor	
Ambient Temp.	5~40°C	
Relative Humidity	80%	
Power Consumption	15W	
Power Supply	100~240V, 50/60Hz	
External Size(W*D*H)	475*265*110mm	
Package Size(W*D*H)	540*475*215mm	
Net Weight	5.5kg	
Gross Weight	7.2kg	

123 124