



## Walk-in Fume Hood



Water Sink



Water & Gas Remote  
Control Valve



Water & Gas Tap



Application



Application

## ADVANTAGE

1. With memory function in case of power-failure.
2. Operators are available to walk into the fume hood to operate if need.
3. Large room exhaust system, suitable for large laboratory instruments and equipment.

## TECHNICAL PARAMETERS

Model		FH1200(W)	FH1500(W)	FH1800(W)
External Size (W*D*H)		1200*800*2250mm	1500*800*2250mm	1800*800*2250mm
Internal Size (W*D*H)		980*550*1670mm	1280*550*1670mm	1580*550*1670mm
Max Opening		1300mm		
Exhaust Airflow Volume		1150m³/h	1500m³/h	1850m³/h
Inflow Air Velocity		0.3~0.8m/s		
Noise		≤ 62dB		
Vibration		Amplitude ≤5μm		
Illumination		≥800Lux		
LED Lamp		12W*2	16W*2	16W*2
Power Supply		AC220V±10%, 50/60Hz; 110V±10%, 60Hz		
Consumption		400W	500W	800W
Front Window		Manual, 5mm toughened glass,height adjustable		
Material	Exterior	1.0mm cold-rolled steel with bacteria powder coating.		
	Interior	Compact laminate board with good acid and alkali resistance function		
Standard Accessory		External blower , LED lamp, Water tap, Gas tap, PP cup sink, Remote control water valve, Remote control gas valve, Waterproof sockets*4, 4.3 meters Φ300mm PVC exhaust duct		
Sockets		Total load of 4 waterproof sockets: ≤500W		
Package Size (W*D*H)	Main Body	1400*1050*2450mm	1710*1050*2450mm	2010*1050*2450mm
	Exhaust Blower	970*810*720mm	1040*890*710mm	1040*890*710mm
Gross Wight		300KG	340KG	390KG