

Rotating Mixer





MX-RD-Pro

MX-RD-E

Features:

- * LCD display of speed and time(MX-RD-Pro).
- * Adjustable mixing angle from 0 to 90° (MX-RD-Pro).
- * Material of the plate: Stainless steel with oxidation coating (MX-RD-E), Stainless Steel (MX-RD-Pro).
- * Material of the clip: Plastic (MX-RD-E), Stainless Steel (MX-RD-Pro).
- * Speed range from 10 to 70rpm(MX-RD-Pro). Adjustable speed range from 0 to 80rpm(MX-RD-E).
- * A wide variety of accessories are available.

Accessories for MX-RD-Pro: (Only 18900162 is standard accessory)



Cat. No.: 18900160

60*1.5ml centrifuge tube

Type 1 plate



Cat. No.: 18900161

16*15ml centrifuge tube

Type 2 plate





Cat. No.: 18900140 Plate support rods 4pcs in a group, use with plates 8*50ml centrifuge tube

Stainless steel clip

Plastic clip

Cat No.: 18900196, for 1.5ml centrifuge tube Cat No.: 18900197, for 15ml centrifuge tube

Cat No.: 18900198, for 50ml centrifuge tube

Cat No.: 18900327, for 1.5ml centrifuge tube

Cat No.: 18900328, for 15ml centrifuge tube

Cat No.: 18900329, for 50ml centrifuge tube

Technical Parameters:

| Model | MX-RD-E | MX-RD-Pro |
|-----------------------|------------------------------------|----------------------|
| Item No. | 8031412000 | 8031412100 |
| Speed Range | 0~80rpm | 10~70rpm |
| Inclining Angle Range | 1 | 0°~90° |
| Timing Range | 1 | 1~1199min |
| Operation Mode | Continuous | Continuous or Timing |
| Display | Scale | LCD |
| Motor Type | DC motor | |
| Ambient Temp. | 5-40°C | |
| Relative Humidity | 80% | |
| Protection Type | IP21 | |
| Consumption | 20W | 40W |
| Power Supply | 100~240V,50/60Hz | |
| Standard Accessories | 18900327 and 18900328 and 18900329 | 18900162 |
| External Size(W*D*H) | 220*300*310mm | 210*280*300mm |
| Package Size(W*D*H) | 370*450*420mm | 370*410*440mm |
| Gross Weight | 5kg | 7kg |

Vertical Rotating Mixer





MX-RL-Pro

MX-RL-E Features:

- * Electronic adjustment of speed and time(MX-RL-Pro).
- * LCD display indicates the speed and time for MX-RL-Pro.
- * Speed range from 0 to 70rpm(MX-RL-Pro), adjustable speed range from 0 to 80 rpm(MX-RL-E).
- * Material of the tube holder: Stainless steel with oxidation coating (MX-RL-E), Stainless Steel (MX-RL-Pro).
- * Material of the clip: Plastic (MX-RL-E), Stainless Steel (MX-RL-Pro).
- * Three clip sizes are selectable, suit for the tubes: 1.5ml, 15ml, 50ml.
- * A wide variety of accessories are available.





Cat No.: 18900196, for 1.5ml centrifuge tube Cat No.: 18900197, for 15ml centrifuge tube Cat No.: 18900198, for 50ml centrifuge tube



Plastic clip

Cat No.: 18900327, for 1.5ml centrifuge tube Cat No.: 18900328, for 15ml centrifuge tube Cat No.: 18900329, for 50ml centrifuge tube

Optional Tube Holder for MX-RL-Pro: (18900147 or 18900145 can be selected as the standard accessory)



Cat. No.: 18900142

Held horizontally

For 48*1.5ml centrifuge



Cat. No.: 18900143

Held horizontally

For 24*15ml centrifuge



Held horizontally

Cat. No.: 18900144 For 24*50ml centrifuge



Held vertically

Cat. No.: 18900145 For 32*1.5ml centrifuge For 16*15ml centrifuge Held vertically



For 16*50ml centrifuge Held vertically

Technical Parameters:

| Model | MX-RL-E | MX-RL-Pro |
|----------------------|------------------------------------|----------------------|
| Item No. | 8031402000 | 8031402100 |
| Speed Range | 0~80rpm | 10~70rpm |
| Timing Range | 1 | 1~1199min |
| Operation Mode | Continuous | Continuous or Timing |
| Display | Scale | LCD |
| Motor Type | DC motor | |
| Ambient Temp. | 5-40°C | |
| Relative Humidity | 80% | |
| Protection Type | IP21 | |
| Consumption | 20W | 40W |
| Power Supply | 100~240V,50/60Hz | ** |
| Standard Accessories | 18900327 and 18900328 and 18900329 | 18900147 or 18900145 |
| External Size(W*D*H) | 530*150*190mm | 510*220*260mm |
| Package Size(W*D*H) | 630*310*380mm | 630*310*380mm |
| Gross Weight | 3kg | 9kg |

125 126