

Rotating Mixer





MX-RD-Pro

MX-RD-E

- Features: * LCD display of speed and time(MX-RD-Pro).
- * Adjustable mixing angle from 0 to 90° (MX-RD-Pro).
- * Material of the plate: Stainless steel with oxidation coating (MX-RD-E), Stainless Steel (MX-RD-Pro).
- * Material of the clip: Plastic (MX-RD-E), Stainless Steel (MX-RD-Pro).
- * Speed range from 10 to 70rpm(MX-RD-Pro). Adjustable speed range from 0 to 80rpm(MX-RD-E).
- * A wide variety of accessories are available.

Accessories for MX-RD-Pro: (Only 18900162 is standard accessory)









Stainless steel clip

Plastic clip

Cat No.: 18900196, for 1.5ml centrifuge tube Cat No.: 18900197, for 15ml centrifuge tube

Cat No.: 18900198, for 50ml centrifuge tube

Cat No.: 18900327, for 1.5ml centrifuge tube

Cat No.: 18900328, for 15ml centrifuge tube

Cat No.: 18900329, for 50ml centrifuge tube

Cat. No.: 18900160 Type 1 plate 60*1.5ml centrifuge tube

Cat. No.: 18900161 Type 2 plate 16*15ml centrifuge tube

Cat. No.: 18900162 Type 3 plate 8*50ml centrifuge tube

Cat. No.: 18900140 Plate support rods 4pcs in a group, use with plates

Technical Parameters:

Model	MX-RD-E	MX-RD-Pro
Item No.	8031412000	8031412100
Speed Range	0~80rpm	10~70rpm
Inclining Angle Range	1	0°~90°
Timing Range	1	1~1199min
Operation Mode	Continuous	Continuous or Timing
Display	Scale	LCD
Motor Type	DC motor	
Ambient Temp.	5-40°C	
Relative Humidity	80%RH	
Protection Type	IP21	
Consumption	20W	40W
Power Supply	AC100~240V, 50/60Hz	
Standard Accessories	18900327 and 18900328 and 18900329	18900162
External Size(W*D*H)	220*300*310mm	210*280*300mm
Package Size(W*D*H)	425*320*415mm	620*300*370mm
Gross Weight	5kg	7kg

Vertical Rotating Mixer





Features:

MX-RL-E

MX-RL-Pro

- * Electronic adjustment of speed and time(MX-RL-Pro).
- * LCD display indicates the speed and time for MX-RL-Pro.
- * Speed range from 10 to 70rpm(MX-RL-Pro), adjustable speed range from 0 to 80 rpm(MX-RL-E).
- * Material of the tube holder: Stainless steel with oxidation coating (MX-RL-E), Stainless Steel (MX-RL-Pro).
- * Material of the clip: Plastic (MX-RL-E), Stainless Steel (MX-RL-Pro).
- * Three clip sizes are selectable, suit for the tubes: 1.5ml, 15ml, 50ml.
- * A wide variety of accessories are available.





Cat No.: 18900196, for 1.5ml centrifuge tube

Cat No.: 18900197, for 15ml centrifuge tube Cat No.: 18900198, for 50ml centrifuge tube

Plastic clip

Cat No.: 18900327, for 1.5ml centrifuge tube

Cat No.: 18900328, for 15ml centrifuge tube Cat No.: 18900329, for 50ml centrifuge tube

Optional Tube Holder for MX-RL-Pro: (18900147 or 18900145 can be selected as the standard accessory)















Cat. No.: 18900142 For 48*1.5ml centrifuge tube Held horizontally

Cat. No.: 18900143 For 24*15ml centrifuge Held horizontally

Held horizontally

For 24*50ml centrifuge For 32*1.5ml centrifuge Held vertically

For 16*15ml centrifuge Held vertically

For 16*50ml centrifuge Held vertically

Technical Parameters:

Model	MX-RL-E	MX-RL-Pro
Item No.	8031402000	8031402100
Speed Range	0~80rpm	10~70rpm
Timing Range	1	1~1199min
Operation Mode	Continuous	Continuous or Timing
Display	Scale	LCD
Motor Type	DC motor	Brushless DC motor
Ambient Temp.	5-40°C	
Relative Humidity	80%RH	
Protection Type	IP21	
Consumption	20W	40W
Power Supply	AC100~240V, 50/60Hz	
Standard Accessories	18900327 and 18900328 and 18900329	18900147 or 18900145
External Size(W*D*H)	530*150*190mm	510*220*260mm
Package Size(W*D*H)	620*300*370mm	620*300*370mm
Gross Weight	3kg	9kg

125 126