



## AC Series Class II A2 Biological Safety Cabinet



**Color Screen**  
Real-time and clearer display of  
various values and appointment  
timing function.



**Anti-paper  
dust  
structure**




The front window glass  
can be lowered below  
the operating area




**Work Zone**  
Work zone, made of 304 stainless steel,  
is surrounded by negative pressure.



**Foot Switch**  
Adjust front window height by  
foot during experiment, to avoid  
airflow turbulence caused by arm  
movement.



**Remote Control**  
All functions can be realized  
with it, making the operation  
much easier and more convenient.



**Front Window**  
Motorized, Two-layer laminated  
toughened glass ≥6mm, Anti UV.



**Footmaster Caster**  
Universal caster with brake  
and leveling feet.



**Cabinet Support Block**  
Easy to lift, prevent hand pressing



**Iron hook support  
rod for panel support**



**UV Lamp**  
Emission of 253.7 nanometers for  
most efficient decontamination.

## ADVANTAGE

1. Small dimension, save space.
2. Centrifugal fan, speed adjustable. ULPA filter.
3. Motorized front window: The front window is motorized for convenient, one-hand operation.
4. Audio and visual alarm: Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm.
5. Time reserve function: This can save 30 minutes waiting time after activating the cabinet and the sterilization time after experiment.
6. Remote control: Each function can be realized 6 meters away from the cabinet by remote control, which can protect the operator under emergency.
7. Large LCD display: Operators can check detailed status of the cabinet, such as inflow and downflow velocity, work area temperature and humidity, filter pressure, UV working time and filter working time, filter life indicator etc.
8. With memory function in case of power-failure.
9. Interlock function: UV lamp and front window; UV lamp and blower, LED lamp; blower and front window.

## TECHNICAL PARAMETERS

Model	BSC-700 II A2-Z
External Size (W*D*H)	700*650*1920mm (700*650*1280mm without base stand)
Internal Size (W*D*H)	600*500*540mm
Tested Opening	Safety height 200mm
Max Opening	380mm
Inflow Velocity	0.53±0.025m/s
Down Flow Velocity	0.33±0.025m/s
ULPA Filter	Two, 99.9995% efficiency at 0.12μm, filter life indicator
Front Window	Motorized
Noise	≤65 dB
UV Lamp	15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination
LED Lamp	8W*2
Illumination	≥1000Lux
Consumption	≤500W
Socket	Two, total load of two sockets: 500W
Display	LCD display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.
Control System	70% air recirculation, 30% air exhaust
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm, abnormal power failure
Material	Work Zone: 304 stainless steel Main Body: Cold-rolled steel with anti-bacteria power coating
Work Surface Height	750mm with base stand
Power Supply	AC220V 50/60Hz; 110V 60Hz
Standard Accessory	Cabinet*1, LED Lamp*2, UV lamp*2, Remote control, Drain valve*1, Waterproof Socket*2, Foot switch
Optional Accessory	Water and gas tap, Electric height adjustable base stand, Armrest, Base stand*1
Package Size (W*D*H)	Without Base Stand 800*760*1470mm With Base Stand 800*900*1470mm
Gross Weight	Without Base Stand 130kg With Base Stand 154kg