



AC Series Class II A2 Biological Safety Cabinet




The front window glass can be lowered below the operating area



Work Zone

Work zone, made of 304 stainless steel, is surrounded by negative pressure.



Remote Control

All functions can be realized with it, making the operation much easier and more convenient.



Footmaster Caster

Universal caster with brake and leveling feet.



Iron hook support rod for panel support



Color Screen

Real-time and clearer display of various values and appointment timing function.




Anti-paper dust structure

The base stand is optional



Foot Switch

Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.




Front Window

Motorized, Two-layer laminated toughened glass $\geq 6\text{mm}$, Anti UV.



Cabinet Support Block

Easy to lift, prevent hand pressing



UV Lamp

Emission of 253.7 nanometers for most efficient decontamination.

ADVANTAGE

1. 4.7-inch color display: real-time and clearer display of various values and appointment timing function.
2. The power-on password can be set to prevent mis-operation by irrelevant personnel.
3. Automatically adjust the wind speed.
4. Power-failure memory, restore the state before power-failure, and have a visual reminder to alarm.
5. Interlocking function: UV lamp and front window; UV lamp and fan; fan and front window.
6. It has an appointment timing function, which can automatically set the timing of turning on, turning off and the running time of the UV lamp, fan, and socket.
7. The rear of the operating area is equipped with anti-paper dust structure to prevent paper scraps from entering the air duct cavity.

TECHNICAL PARAMETERS

Model	BSC-700IIA2-Z	
External Size (W*D*H)	700*650*1920mm (700*650*1280mm without base stand)	
Internal Size (W*D*H)	600*500*540mm	
Tested Opening	Safety height 200mm	
Max Opening	380mm	
Inflow Velocity	0.53 $\pm$ 0.025m/s	
Down Flow Velocity	0.33 $\pm$ 0.025m/s	
ULPA Filter	Two, 99.9995% efficiency at 0.12 μm , filter life indicator	
Front Window	Motorized	
Noise	$\leq 65\text{ dB}$	
UV Lamp	15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination	
LED Lamp	8W*2	
Illumination	$\geq 1000\text{Lux}$	
Consumption	$\leq 500\text{W}$	
Socket	Two, total load of two sockets: 500W	
Display	LCD display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.	
Control System	70% air recirculation, 30% air exhaust	
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm, abnormal power failure	
Material	Work Zone: 304 stainless steel Main Body: Cold-rolled steel with anti-bacteria power coating	
Work Surface Height	750mm with base stand	
Power Supply	AC220V 50/60Hz; 110V 60Hz	
Standard Accessory	Cabinet*1, LED Lamp*2, UV lamp*2, Remote control, Drain valve*1, Waterproof Socket*2, Foot switch	
Optional Accessory	Water and gas tap, Electric height adjustable base stand, Armrest, Base stand*1	
Package Size (W*D*H)	Without Base Stand	800*760*1470mm
	With Base Stand	800*900*1470mm
Gross Weight	Without Base Stand	130kg
	With Base Stand	154kg