

AC Series Class II A2 Biological Safety Cabinet



Color Screen

Real-time and clearer display of various values and appointment timing function.



Anti-paper
dust
structure



The front window glass can be lowered below the operating area

The base stand is optional




Work Zone

Work zone, made of 304 stainless steel, is surrounded by negative pressure.




Foot Switch

Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.



Remote Control

All functions can be realized with it, making the operation much easier and more convenient.



Front Window

Motorized, Two-layer laminated toughened glass ≥6mm, Anti UV.



Footmaster Caster

Universal caster with brake and leveling feet.




Cabinet Support Block

Easy to lift, prevent hand pressing



Iron hook support rod for panel support



UV Lamp

Emission of 253.7 nanometers for most efficient decontamination.

ADVANTAGE

1. Small dimension, save space.
2. Centrifugal fan, speed adjustable. ULPA filter.
3. Motorized front window: The front window is motorized for convenient, one-hand operation.
4. Audio and visual alarm: Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm.
5. Time reserve function: This can save 30 minutes waiting time after activating the cabinet and the sterilization time after experiment.
6. Remote control: Each function can be realized 6 meters away from the cabinet by remote control, which can protect the operator under emergency.
7. Large LCD display: Operators can check detailed status of the cabinet, such as inflow and downflow velocity, work area temperature and humidity, filter pressure, UV working time and filter working time, filter life indicator etc.
8. With memory function in case of power-failure.
9. Interlock function: UV lamp and front window; UV lamp and blower, LED lamp; blower and front window.

TECHNICAL PARAMETERS

Model	BSC-700 II A2-Z	
External Size (W*D*H)	700*650*1920mm (700*650*1280mm without base stand)	
Internal Size (W*D*H)	600*500*540mm	
Tested Opening	Safety height 200mm	
Max Opening	380mm	
Inflow Velocity	0.53±0.025m/s	
Down Flow Velocity	0.33±0.025m/s	
ULPA Filter	Two, 99.9995% efficiency at 0.12μm, filter life indicator	
Front Window	Motorized	
Noise	≤65 dB	
UV Lamp	15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination	
LED Lamp	8W*2	
Illumination	≥1000Lux	
Consumption	≤500W	
Socket	Two, total load of two sockets: 500W	
Display	LCD display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.	
Control System	70% air recirculation, 30% air exhaust	
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm, abnormal power failure	
Material	Work Zone: 304 stainless steel Main Body: Cold-rolled steel with anti-bacteria power coating	
Work Surface Height	750mm with base stand	
Power Supply	AC220V 50/60Hz; 110V 60Hz	
Standard Accessory	Cabinet*1, LED Lamp*2, UV lamp*2, Remote control, Drain valve*1, Waterproof Socket*2, Foot switch	
Optional Accessory	Water and gas tap, Electric height adjustable base stand, Armrest, Base stand*1	
Package Size (W*D*H)	Without Base Stand	800*760*1470mm
	With Base Stand	800*900*1470mm
Gross Weight	Without Base Stand	130kg
	With Base Stand	154kg