

### Table Top Dental Sterilizer



The printer is optional

**Features:**

- \* The sterilizer adopts easy-clean open type water tank which can support repeated program running if fully injected with water.
- \* The sterilizer adopts high-efficiency low noise vacuum system which has excellent effects.
- \* The system has various programs that include packed items, unpacked items, BD testing program, vacuum testing program and drying function.
- \* Optional mini printer can be attached to record the process of sterilization.

**Technical Parameters:**

Model	BKM-Z8BII	BKM-Z12BII
Capacity	8L	12L
Chamber Size	φ170*310mm	φ200*360mm
Water Tank Capacity	3L	
Sterilization Class	Class B	
Chamber Material	SUS304	
Sterilizing Temperature	121°C, 134°C	
Vacuum Degree	-0.09MPa	
Environment Temperature	0-40°C	
Consumption	1.8kw	
Sterilizer Max Temperature	138°C	
Power Supply	Standard: 220V±10%, 50/60Hz; Optional: 110V±10%, 50/60Hz. Wiring Method: Plug	
Packing Size	670*550*500mm	670*550*500mm
Gross Weight	46kg	46kg

### Portable Autoclave

**Range of Application:**

It's desk-top autoclave sterilizer which is designed for the hospital, clinic, lab, etc. It's mostly suitable for sterilizing of surgical, dental instruments, glassware, culture medium and biological dressing, food and goods, etc.

**Features:**

- \* Easy operation, safe and reliable.
- \* The sealing ring is made of silicon rubber.
- \* Two safety valves keep double safety (for timing control type).
- \* It has self-adjustment function (for timing control type)
- \* It is well sealed and effectively prevents steam leakage.
- \* Over temperature & over pressure auto-protection.
- \* Electric or LPG heating (for Dual fuel Type).
- \* Immersion type electric heating pipe, thermal efficiency is high, stainless steel material tube is durable to use.
- \* Double groove pressure gauge, could clearly indicate, convenient observation, reliable performance.
- \* When at lower water level, or at the end of heat preservation time, have buzzer alarm, timing control type will automatically stop heating (for timing control type).



Timing control type



Anti-dry out type



Dual fuel type

**Technical Parameters:**

Model	BKM-P18(T)	BKM-P24(T)	BKM-P18(F)	BKM-P24(F)	BKM-P18(B)	BKM-P24(B)
Type	Timing control type		Anti-dry out type		Dual fuel Type	
Capacity	18L	24L	18L	24L	18L	24L
Chamber Size(mm)	φ280*260	φ280*390	φ280*260	φ280*390	φ280*260	φ280*390
Time Setting	0~99min		NO			
Temperature Setting	126°C					
Consumption	2KW					
Power Supply	Standard: AC220V,50Hz; Optional: AC110V,60Hz. Wiring Method: Plug					
Working Pressure	0.14-0.16Mpa					
Package Size(W*D*H)mm	410*410*630	410*410*750	410*410*520	420*420*630	410*410*430	410*410*550
Gross Weight(kg)	14	15	18	19	16	17