



## Laminar Flow Pathology Workstation



360°rotatable and adjustable spotlight, convenient for taking materials



Formaldehyde perfusion universal faucet, The telescopic faucet is convenient for cleaning the countertop



Foldable hot and cold faucet



Real-time display of intelligent control parameters, Human body induction switch is easy to operate

## APPLICATION

Pathological sampling bench is widely used in hospital pathology department, pathology laboratory, etc. Reasonable ventilation system protects operator away from the harmful gas produced by the formalin during sampling. The hot & cold water system ensures it can adapt work in different climates.

## ADVANTAGE

1. The open table design is adopted, and the front and rear of the operation area are unobstructed to ensure the maximum experimental space.
2. Airflow pattern design with top air supply and bottom exhaust.
3. Intelligent control system adopts LCD operation panel.
4. The whole machine is made of 304 stainless steel, easy to clean.
5. Standard formaldehyde filling device, built-in liquid tank, with liquid filling accessories and low liquid level alarm system, convenient for filling formaldehyde.

## TECHNICAL PARAMETERS

Model	QCT-1800L
External Size	1800*800*2000mm
Operating Table Size	1455*490mm
Operating Table Adjustable Height	800-950mm
Airflow Pattern	Top air supply and bottom exhaust
Standard Function	Formaldehyde perfusion system, table lifting system, human body induction Switch, touch control screen, spotlight, UV lamp, LED lighting, telescopic faucet, folding hot and cold faucet, motorized non-return valve, sink, transparent socket
Optional Function	LED floor-standing magnifying glass, specimen preparation board, stainless steel tissue box, gross specimen imaging system, portable display stand, dryer, and exhaust fan.
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz
Net Weight	380kg
Packing Size(W*D*H)	2000*960*2300mm
Gross Weight	410kg