

E-mail: export@biobase.com



### LED Display

Temperature and humidity, with fan, UV lamp, fluorescent lamp, heating lamp control buttons.



#### **Footmaster Caster**

Universal caster with brake and leveling feet, easy to move and fix



#### Depressurization Type Water Tank

With automatic feed water system, labor saving



Filters Pattern

## INTRODUCTION

Chicken isolator is Positive pressure isolator.

BCI-I Chicken Isolator is designed for SPF chicken feeding and poultry disease testing.

## **ADVANTAGE**

- 1. Automatic water supply system, adjustable height drinking tank.
- 2. Special sealing design, ensure good sealing performance.
- 3. Manipulation of the chicken can be realized via gloves from both sides.
- 4. Adopt full 304 stainless steel material, high quality accessories, such as Butyl gloves, HEPA filter etc.
- Filtration system, can protect animals, environment and operator.
  Pre-filter→ main HEPA filter→Filter cotton.
- 6. Three sterilization ways available.
  - 1) UV lamp for sterilization.
  - 2 Reserved hole for hot steam sterilization.
  - 3 Reserved hole for disinfectant spraying sterilization.
- 7. Unique defecation system & fecal leakage shelf. Animal wastes drop from shelf to bottom fecal collection film, then pull of collecting film and clean out wastes conveniently and quickly, reduce the cleaning frequency.
- 8. The inner wall of the glove mouth is equipped with a sliding sealing plate, which can seal the glove mouth when there is no operation.
- 9. The heating lamp adopts high temperature resistant lamp holder, and has protective cover to prevent chickens from touching, safe and reliable.

# TECHNICAL PARAMETERS

Model	BCI-I
External Size (W*D*H)	2200*850*1800mm
Animal Activity Area(W*D*H)	1600*750*820mm
Waste Collection Area(W*D*H)	1600*750*250mm
Display	LED display: temperature,humidity adjustable(10-50℃), with fluorescent lamp,
	UV lamp, heating lamp, fan button
Air Change Rate	≥20 times/h
Airflow Velocity	0.1m/s~0.2m/s within the chicken living space
Falling Bacteria (numbers/utensil/hour)	0
Filter	Pre-filter, Mid-filter, HEPA (H14) filter
Noise	≤70dB(A)
Alarm	High and low temperature alarm
Caster	Universal caster with brake and leveling feet
Rated Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Rated Consumption	700W
Gross Weight	279kg
Package Size (W*D*H)	2430*1010*2070mm
Standard Accessories	Pre-filter*2, HEPA filter*2, Mid-filter*2, UV lamp, heating lamp*2, high quality butyl
	gloves*6(pairs), feeding and drinking system

\_ 139/140