

## Laboratory Refrigerator



BPR-5V650



BPR-5V368



BPR-5V1000

### Technical Parameters

Model	BPR-5V368	BPR-5V650	BPR-5V1000
Type (shelf / drawer)	5 layers shelves	5 layers/10 shelves	
Material	Plastic-coated steel wire		
Refrigeration Mode	Air-cooled		
Defrosting Mode	Automatic		
Refrigerant/g	R134a, CFC free/120g	R134a, CFC free/120g	R134a, CFC free/175g
Noise	55dB(A)	60dB(A)	
Ambient Temp.	10~32°C		
Temp. Range	5±3°C		
Temp. Accuracy	0.1°C		
Evaporator	Copper tube and aluminum fin		
Condenser	Bundy tube		
Sensor	NTC		
Thermostat	Electronic thermostat		
Door	Electric heating glass door		
Probe access port	Number	1 pcs	
	Inner Diameter	φ23	
Display	LED		
Interface	USB		
Power Supply	220V/50Hz		
Power	230W	537W	
Current	1.65A	3.2A	
Internal Material	Rolled aluminum board	Sprayed steel plate	
External Material	Spray steel plate	Sprayed steel plate	
Lagging	Foamed polyurethane cyclopentane		
Volume	368L	650L	1000L
Standard Accessories	High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door open alarm, LED lamp, USB port, Probe access port		
Optional Accessories	Printer		
Net Weight	90kg	189kg	212kg
Gross Weight	105kg	235kg	262kg
Internal Size(W*D*H)	566*475*1290mm	1100*454*1325mm	1100*684*1325mm
External Size(W*D*H)	650*600*2010mm	1220*630*1885mm	1220*860*1885mm
Package Size(W*D*H)	692*740*2230mm	1340*750*2100mm	1340*980*2100mm