

Laboratory Refrigerator



BPR-5V628



BPR-5V650



BPR-5V968

Technical Parameters

Model	BPR-5V628	BPR-5V650	BPR-5V968
Capacity	628L	650L	968L
Temp. Range	2~8°C		
Temp. Accuracy	0.1°C		
Control System	Microprocessor control, Digital tube display		
Alarm	High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door ajar alarm		
Refrigeration Type	Air-cooled		
Refrigerant	R134a, CFC-free, 175g	R290a, CFC free, 150g	R134a, CFC-free, 175g
Condenser & Evaporator	Copper tube and aluminum fin, Bundy tube		
Defrost	Auto defrost		
Construction	Structure	Unibody design & mono-assembly foaming (Polyurethane cyclopentane insulation material)	
	Internal Material	Spraying steel plate	
	External Material	Spraying steel plate	
Shelves	10 pcs		
Door	Electric-heating glass door, no condensation		
Consumption	537W/704VA	300W/330VA	537W/704VA
Power Supply	220V, 50/60Hz; 110V, 60Hz		
Standard Accessories	LED lamp, USB port, temp. test port		
Optional Accessories	Temp. recorder, printer, shelf, RS485 port		
External Size (W*D*H)mm	1220*630*1885		1220*860*1885
Package Size (W*D*H)mm	1340*750*2100		1340*980*2100
Gross Weight	223kg		256kg