

Air Shower



Air shower is a necessary passage for people entering clean room in order to minimize the amount of particulate contaminant, to achieve workplace strict clean purification standards. Personnel move through the air shower while particulate contaminants are blown off by the clean high-speed air. Then the dust cannot be brought into clean area.

Features

1. Photoelectric sensor, automatic blowing.
2. Adopt with circulation wind to ensure the cleanness of shower area under non-shower status.
3. Double doors by electric interlock.
4. LED display with adjustable blowing time (0~99s).
5. HEPA Filter, Class 100 cleanness.

Model	AS-1P1S	AS-1P2S	AS-2P2S
External Size(W*D*H)	1300*1000*2050mm	1500*1000*2050mm	1500*2000*2050mm
Internal Size(W*D*H)	800*900*1930mm	800*900*1930mm	800*1900*1930mm
HEPA Filter	99.995% efficiency at 0.3µm		
Spraying Wind Speed	25m/s		
Air Shower Time	0~99s(adjustable)		
No.of SS Nozzles	6	12	24
Fluorescent Lamp	12W*1	12W*1	12W*1
Consumption	550W	1100W	2200W
Cabinet Material (Optional)	1. Full cold-rolled steel with powder coating. 2. Internal stainless steel, external with cold-rolled steel. 3. Full stainless steel.		
Door Material (Optional)	1.Cold-rolled steel with powder coating. 2. Stainless steel.		
Chassis	Stainless steel		
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz		
Gross Weight	300kg	400kg	700kg
Package Size(W*D*H)	1400*1200*2200mm	1600*1200*2200mm	1600*2200*2200mm

Pass Box



Pass Box

Air Shower Box

Pass Box is used to transfer goods between rooms of different clean levels of clean room. It can reduce times of opening door, prevent the air convection between different rooms and minimize the pollution extent.

Type	Air Shower Pass Box			Pass Box		
Model	ASPB-01	ASPB-02	ASPB-03	PB-01	PB-02	PB-03
External Size(W*D*H)mm	660*570*1000	760*670*1100	860*770*1200	660*570*580	760*670*680	860*770*780
Internal Size(W*D*H)mm	500*500*500	600*600*600	700*700*700	500*500*500	600*600*600	700*700*700
Material	304Stainless steel					
Interlock	Electronical					
UV Lamp	8W*1					
HEPA Filter	Efficiency≥99.995% at 0.3um			/		
Clean Air Speed	0.36~0.54m/s			/		
Power Supply	220V, 50Hz; 110V, 50/60Hz					
Gross Weight (Kg)	80	100	120	55	70	90
Packing Size(W*D*H) mm	780*700*1250	880*800*1350	980*900*1450	780*700*770	880*800*870	980*900*970