


Wrist Action Shaker



- Features:**
- * The leakage current and overcurrent protection system ensures the safety of operators.
 - * It can accommodate containers with a diameter of up to 80mm. The load capacity on each side is 6 kilograms.
 - * Suitable for various containers such as test tubes, beakers, wide-mouth bottles, narrow-mouth bottles, distillation bottles, separating funnels, straight-mouth bottles, etc.
 - * It is made of 304 stainless steel.
 - * Reliable core components, such as servo motor etc.

Technical Parameters:	
Model	SK-S810
Max Capacity	12*500ml or 8*1000ml
Display	5-inch high-definition LCD touchscreen
Shaking Motion	Angle oscillation type
Speed Range	50-600rpm
Speed Accuracy	±1rpm
Shaking Angel	3°/ 6°/ 9°/ 10°/ 12° (Choose any one)
Shaking Diameter	13.3cm
Time Range	0-999s/min/h
Programming	30 user-written programs
Safety Function	Automatic operation, automatic stop, timed operation, clock display, call recovery, parameter memory, speed storage
Power Supply	AC220V±10%; 50/60Hz(Standard); AC110V±10%, 50/60Hz(Optional)
Consumption	400W
External Size(L*W*H)	360*410*310mm(Without arm); 970*410*310mm(With arm)
Packing Size(L*W*H)	520*460*480mm
Net Weight	50kg
Gross Weight	63kg

Mixer
Multi-Tube Vortex Mixer



- Features:**
- * Up to 96 samples can be processed at one time, and the rotation speed can reach 2500rpm.
 - * Run time and pause time can be set.
 - * Configure various types of sponge test tube racks.
 - * Button-type jog mode, double switch design.
 - * Power-off memory function, saving setup time.
 - * Accelerates uniformly, effectively avoiding sample splashing.
 - * Three working modes of jog, continuous and intermittent pulse can be selected at will.
 - * LED display speed and time, simple operation panel, precise control by microprocessor.

Technical Parameters:	
Model	BHY-2500
Speed Range	500-2500rpm
Speed Regulation Accuracy	±1rpm
Amplitude	4mm
Time Setting Range	1s-99h59min
Pulse Interval Timing Range	1s-99s
Pulse Operation Timing Range	1s-99min59s
Consumption	120W
Power Supply	AC100-240V, 50/60Hz
Standard Accessory	I, II, III, IV
External Size (L*W*H)	438*301*429mm
Package Size (W*D*H)	530*380*510mm
Gross Weight	27kg

Accessories:			
Model	Pore Diameter	Compatible Type	Size
I	48-Well Virus Sampling Tube Rack	20ml or 30ml virus sampling tube	272*205*50mm
II	96-Well Virus Sampling Tube Rack	7ml or 10ml virus sampling tube 10ml or 15ml centrifuge tube	296*202*50mm
III	Replaceable Tray Pad	/	302*212*25mm
IV	Φ25-Φ29mm	50ml centrifuge tube	300*210*45mm