

-25°C Freezer

Features

- 1.Digital temperature display.
- 2.The safety lock can prevent random opening.
- 3.Baskets made of steel wire are convenient to store articles.
- 4.Round corner design of doors and the body provides luxury and elegance.
- 5.Delayed start and safe stop interval between restart and being terminated, ensure reliable running.



BDF-25H305

Technical Parameters

Model		BDF-25H305
External Size(W*D*H) mm		1148*740*872
Capacity		305L
Temp. Range		-10℃~-25℃
Temp. Accuracy		0.1℃
Control System		Microprocessor control&LED display
Alarm		High or low temperature alarm, sensor failure alarm, thermostat alarm, power failure alarm
Refrigeration Type		Direct refrigeration
Refrigerant		R134a
Condenser&Evaporator		Internal-mounted condenser and finned evaporator
Construction	Structure	Whole foaming, freon cyclopentane/isopentane high density polyurethane foam
	Internal Material	Spraying steel plate
	External Material	Spraying steel plate
Basket		none
Consumption		106W
Power Supply		AC220V±10%,50/60Hz; AC110V±10%,60Hz
Package Size(W*D*H)mm		1223*777*1005
Gross Weight		87kg

-40°C Freezer



90L



268L

Technical Parameters

Model		BDF-40V90	BDF-40V268II
External Size(W*D*H)		600*610*945mm	690*744*1631mm
Internal Size(W*D*H)		440*447*640mm	520*567*1013mm
Capacity		90L	268L
Type		Vertical	
Temp. Range		-15℃~-40℃	
Temp. Accuracy		0.1℃	
Control System		Microprocessor Control; LED Display	
Alarm		BDF-40V90: High or low temperature alarm,sensor failure alarm,power failure alarm,door open alarm.	High or low temperature alarm, door ajar alarm, power failure alarm, sensor failure alarm
Refrigeration Type		Direct Refrigeration	
Refrigerant		R290	CFC free
Compressor		Unicompressor,imported famous brand compressor	International well-known brand
Construction	Structure	Uniboday design	
	Internal Material	304 stainless steel	Stainless steel
	External Material	Sprayed steel plate	
Drawer/Shelf		2 pcs shelves	3pcs shelves,Stainless Steel
Consumption		252W	335W
Power Supply		AC220V±10%, 50/60HZ	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Package Size		725*735*1160mm	810*860*1820mm
Gross Weight		83kg	165kg