

Benchtop pH Meter



- Features:**
 - * Use a large screen and LCD display.
 - * PH-25: pH; mV, PH-3CU: pH; mV; temperature
 - * Equipped with USB communication interface, REX data acquisition software(For PH-3CU).
 - * PH-25 has a manual temperature compensation function, PH-3CU has the functions of manual and automatic temperature compensation.
 - * One or three-point calibration.
- Accessories:**

Meter; pH composite electrode; calibration solution

Technical Parameters:

Model		PH-25	PH-3CU
pH	Range	0.00~14.00pH	-2.00~19.99pH
	Resolution	0.01pH	
	Accuracy	±0.02pH ± one digit	±0.01pH ± one digit
	Calibration Points	1~3 points, automatically	
mV	Range	0~1599mV	-1999~1999mV
	Resolution	1mV	
	Accuracy	±1%FS	±1mV ± one digit
Temperature	Range	/	0.0~80.0℃
	Resolution	/	0.1℃
	Accuracy	/	±0.1℃
Temp. Compensation Range		0.0~60.0℃	0.0~80.0℃
Power Requirements		DC (9V, 1.0A)	
External Size(W*D*H)		220*160*65mm	290*210*95mm
Package Size(W*D*H)		330*300*145mm	365*300*215mm
Net Weight		1.5kg	
Gross Weight		2.5kg	