Roller Mixer





Introduction:

Roller mixer is used for mixing blood samples, viscous substances and liquid-solid suspensions, prevention of blood coagulation and immune precipitation etc.

Features:

- * Rocking and Rolling modes for good mixing.
- * LCD displays running speed and timing time.

 * Electronic setting speed and timing time, more correct control
- * Adjustable speed, maximum speed up to 100rpm.
- * Six roller design, suitable for a variety of sample tubes.
- * Timed or continuous operation mode.
 Technical Parameters: DODASE.CC / www.biobase.com

Model	BK-RX6	BK-RX6F
Mixing Mode	Rocking & Rolling	
Speed Range	10-100 rpm	
Rocking Amplitude	24mm	
Number of Roller	6 pcs	
Roller Length	280mm	
Max. Loading Weight	4Kg	
Operation Mode	Continuous	Continuous or timing
Speed Display	Scale	LCD
Timer	1	Yes
Timer Display	T	LED
Timing Range	1	1min~9999min
Motor Type	Brushless DC motor	
Applicable Specifications	Dia.6-34mm	
Consumption	25W	30W
Power Supply	AC100~240V, 50/60Hz	
Product Size (W*D*H)	468*250*102mm	
Packing Size (W*D*H)	531*312*186mm	
Net Weight	4kg	4.2kg
Gross Weight	5.5kg	5.5kg





MX-T6-Pro

Introduction:

Roller mixer is used for mixing blood samples, viscous substances and liquid-solid suspensions, prevention of blood Notier mixer is used for mixing blood samples, viscous substar coagulation and immune precipitation etc.

Features:

* LCD display indicates the speed and time for MX-T8-Pro.

* Speed range of 10-70rpm.

* Six roller design for gentle rolling and easy to clean.

- Technical Parameters:

Mixing Mode Roc Speed Range 0-7 Rocking Amplitude 24m Number of Roller 6 pc Roller Length 280 Max. Loading Weight 4kg Timing Range /	1312000 king & Rolling Drpm	8031312100 10~70 rpm
Speed Range 0-7 Rocking Amplitude 24m Number of Roller 6 pc Roller Length 280 Max. Loading Weight 4kg Tirning Range / Operation Mode Con Speed Display Sca Tirner /) rpm	iobase.com
Rocking Amplitude 24m Number of Roller 6 pc Roller Length 280 Max. Loading Weight 4kg Timing Range / Operation Mode Con Speed Display Sca Timer /	0 rpm	10~70 rpm
Number of Roller 6 pc Roller Length 280 Max. Loading Weight 4kg Timer / Operation Mode Con Speed Display Sca Timer /		
Roller Length 280 Max. Loading Weight 4kg Timing Range / Operation Mode Con Speed Display Sca Timer /	24mm	
Max. Loading Weight 4kg Timing Range / Operation Mode Con Speed Display Sca Timer /	6 pcs	
Timing Range / Operation Mode Con Speed Display Sca Timer /	280mm	
Operation Mode Con Speed Display Sca Timer /	4kg	
Speed Display Sca Timer /		1~1199min
Timer /	tinuous	Continuous or timing
	le	LCD
Timer display /		Yes
		LCD
Motor Type Brus	h DC motor	Brushless DC motor
Ambient Temp. 5-40	5-40℃	
Relative Humidity 80%	80%RH	
Protection Type IP2	IP21	
Power Consumption 25W	1	30W
Power Supply AC1	AC100~240V,50/60Hz	
External Size(W*D*H) 450	450*250*100mm	
Package Size(W*D*H) 585	585*380*235mm	
Gross Weight 5kg		5kg

163