

Rotating Mixer



BK-RD20



MX-RD-E



MX-RD-Pro

Features:

- * Display of speed and time(BK-RD20 and MX-RD-Pro).
- * Adjustable mixing angle from 0 to 90°(BK-RD20 and MX-RD-Pro).
- * Material of the plate: Carbon steel spraying(BK-RD20); Stainless steel with oxidation coating(MX-RD-E); Stainless steel(MX-RD-Pro).
- * Material of the clip: Plastic (MX-RD-E); Stainless steel(BK-RD20 and MX-RD-Pro).
- * Speed range from 10 to 100rpm(BK-RD20). Speed range from 10 to 70rpm (MX-RD-Pro). Adjustable speed range from 0 to 80rpm(MX-RD-E).
- * A wide variety of accessories are available.

Accessories for BK-RD20:



Stainless steel clip
 Cat No.: 27833, for 1.5ml~2ml centrifuge tube
 Cat No.: 27832, for 10ml~15ml centrifuge tube
 Cat No.: 27831, for 50ml~100ml centrifuge tube



Cat No.: 00577
 1.5ml*60



Cat No.: 00578
 15ml*16



Cat No.: 00579
 50ml*8

Accessories for MX-RD-Pro: (Only 18900162 is standard accessory)



Stainless steel clip
 Cat No.: 18900196, for 1.5ml centrifuge tube
 Cat No.: 18900197, for 15ml centrifuge tube
 Cat No.: 18900198, for 50ml centrifuge tube



Cat. No.: 18900160
 Type 1 plate
 60*1.5ml centrifuge tube



Cat. No.: 18900161
 Type 2 plate
 16*15ml centrifuge tube



Cat. No.: 18900162
 Type 3 plate
 8*50ml centrifuge tube



Cat. No.: 18900140
 Plate support rods
 4pcs in a group, use with plates

Technical Parameters:

Model	BK-RD20	MX-RD-E	MX-RD-Pro
Item No.	/	8031412000	8031412100
Speed Range	10~100rpm	0~80rpm	10~70rpm
Inclining Angle Range	0°~90°	/	0°~90°
Timing Range	1~9999min	/	1~1199min
Operation Mode	Continuous or Timing	Continuous	Continuous or Timing
Display	LED	Scale	LCD
Motor Type	Brushless DC motor	DC motor	
Ambient Temp.	5~40°C		
Relative Humidity	≤80%RH		
Protection Type	/	IP21	
Consumption	30W	20W	40W
Power Supply	AC100~240V, 50/60Hz		
Standard Accessories	00577 or 00578 or 00579	18900327 and 18900328 and 18900329	
External Size(W*D*H)	250*280*332mm	220*300*310mm	210*280*300mm
Package Size(W*D*H)	370*340*420mm	425*320*415mm	620*300*370mm
Gross Weight	7kg	5kg	7kg

Vertical Rotating Mixer



BK-RL20



MX-RL-E



MX-RL-Pro

Features:

- * Electronic adjustment of speed and time(BK-RL20 and MX-RL-Pro).
- * Display indicates the speed and time for BK-RL20 and MX-RL-Pro.
- * Speed range from10 to 100rpm(BK-RL20), speed range from10 to 70rpm (MX-RL-Pro), adjustable speed range from 0 to 80 rpm(MX-RL-E).
- * Material of the tube holder: Stainless steel with oxidation coating(MX-RL-E), Stainless steel(BK-RL20 and MX-RL-Pro).
- * Material of the clip: Plastic(MX-RL-E), Stainless steel(BK-RL20 and MX-RL-Pro).
- * Three clip sizes are selectable, suit for the tubes: 1.5ml, 15ml, 50ml.
- * A wide variety of accessories are available.

Accessories for BK-RL20:



Stainless steel clip
 Cat No.: 27833, for 1.5ml~2ml centrifuge tube
 Cat No.: 27832, for 10ml~15ml centrifuge tube
 Cat No.: 27831, for 50ml~100ml centrifuge tube



Cat No.: 00580
 1.5ml*32



Cat No.: 00581
 1.5ml*48



Cat No.: 00582
 15ml*16



Cat No.: 00583
 15ml*24



Cat No.: 00584
 50ml*16



Cat No.: 00585
 50ml*24

Accessories for MX-RL-Pro: (18900147 or 18900145 can be selected as the standard accessory)



Stainless steel clip
 Cat No.: 18900196, for 1.5ml centrifuge tube
 Cat No.: 18900197, for 15ml centrifuge tube
 Cat No.: 18900198, for 50ml centrifuge tube



Cat. No.: 18900142
 For 48*1.5ml centrifuge tube
 Held horizontally



Cat. No.: 18900143
 For 24*15ml centrifuge tube
 Held horizontally



Cat. No.: 18900144
 For 24*50ml centrifuge tube
 Held horizontally



Cat. No.: 18900145
 For 32*1.5ml centrifuge tube
 Held vertically



Cat. No.: 18900146
 For 16*15ml centrifuge tube
 Held vertically



Cat. No.: 18900147
 For 16*50ml centrifuge tube
 Held vertically

Technical Parameters:

Model	BK-RL20	MX-RL-E	MX-RL-Pro
Item No.	/	8031402000	8031402100
Speed Range	10~100rpm	0~80rpm	10~70rpm
Timing Range	1~9999min	/	1~1199min
Operation Mode	Continuous or timing	Continuous	Continuous or Timing
Display	LED	Scale	LCD
Motor Type	Brushless DC motor	DC motor	Brushless DC motor
Ambient Temp.	5~40°C		
Relative Humidity	≤80%RH		
Protection Type	/	IP21	
Consumption	30W	20W	40W
Power Supply	AC100~240V, 50/60Hz		
Standard Accessories	00580 or 00581 or 00582 or 00583 or 00584 or 00585	18900327 and 18900328 and 18900329	
External Size(W*D*H)	523*237*285mm	530*150*190mm	510*220*260mm
Package Size(W*D*H)	615*330*380mm	620*300*370mm	620*300*370mm
Gross Weight	8.5kg	3kg	9kg