

Constant-Temperature Incubator

Features:

- * Microcomputer-based smart temperature controller.
- * LCD display for setting temperature and the temperature in the chamber, parameter memory and recovery function for the purpose of protection against power failure, computer system halt and data loss; protection and alarming against excessive temperature, failure of sensors, creep and , over-current; sound & light alarming; timing function.
- * Separate temperature limiting and alarming system, automatic suspension in time of exceeding temperature limit (optional).
- * UV sterilizing system (optional).
- * RS-485 portal, capable of being connected with printer or computer, recording variations of temperature parameters (optional).
- * Double door (optional).



Technical Parameters:

Model	BJPX-H50IV	BJPX-H80IV	BJPX-H160IV	BJPX-H270IV
Capacity	50L	80L	160L	270L
Temp.Range	RT+5~65°C			
Temp.Resolution	0.1			
Temp.Fluctuation	±0.5°C			
Temp. Uniformity	±1°C(37°C)			
Time Range	1~9999mins			
Shelves(Standard)	2pcs			
Consumption	250W	300W	400W	600W
PowerSupply	AC220V±10%, 50/60Hz(Standard) AC110±10%, 60Hz(Optional)			
Internal Size(mm)	350*360*410	400*400*500	500*500*650	600*600*750
External Size(mm)	450*520*680	500*560*760	600*620*910	720*690*1020
Packing Size (mm)	550*620*780	600*660*860	700*720*1010	820*790*1120
Gross Weight (kg)	40	47	70	90

Constant-Temperature Incubator

Features:

- * LCD display.
- * Microcomputer temperature controller.
- * Double door design and magnetic door sealing.
- * Castors are equipped for easy movement.
- * The working chamber adopts round angle structure, easy to clean.

Safety Functions:

- * Over temperature protection, temperature sensor malfunction alarm.
- * Parameters can be saved automatically when power off or system error.



Technical Parameters:

Model	BJPX-H35	BJPX-H50II	BJPX-H80II	BJPX-H160II	BJPX-H270II
Capacity	35L	48L	84L	160L	270L
Temp. Range	RT+5~65°C		RT+5~60°C		
Temp. Fluctuation	±0.3°C		±0.3°C		
Time Range	0~5999mins		1~9999mins		
Shelves	2pcs/adjustable			3 pcs/adjustable	
Consumption	200W	437W	502W	580W	688W
Power Supply	Standard:AC220V,50/60Hz; Optional:AC220V,60Hz; AC110V,60Hz		AC220V,50/60Hz(Standard); AC110,60Hz(Optional)		
Internal Size(mm)	340*320*320	350*348*400	410*405*510	505*455*700	600*600*750
External Size(mm)	620*490*490	510*548*740	570*590*850	673*645*1033	768*795*1083
Package Size(mm)	740*600*670	590*650*930	730*700*1030	800*800*1210	930*940*1250
Gross Weight(kg)	31	50	75	99.5	150