

Laboratory Refrigerator



BPR-5V628



BPR-5V650



BPR-5V968

Technical Parameters

Model	BPR-5V628	BPR-5V650	BPR-5V968
Capacity	628L	650L	968L
Temp. Range	2~8°C		
Temp. Accuracy	0.1°C		
Temp. Uniformity	≤2°C		
Temp. Stability	≤3°C		
Recovery Time (Recover to 8°C in an ambient temp. of 32°C)	≤15min		
Cooling Time (Cool down to 6°C in an ambient temp. of 32°C)	≤100min	≤75min	≤100min
Control System	Microprocessor control		
Display	LED		
Alarm	High and low temperature alarm, thermostat fault alarm, door switch alarm, power failure alarm(8h)		
Refrigeration Type	Air-cooling		
Refrigerant	R290/150g	R290a/150g	R290/150g
Compressor	International famous brand compressor/1		
Condenser & Evaporator	Copper tube aluminum fin type		
Defrost	Automatic defrost		
Construction	Polyurethane cyclopentane insulation material		
Material	Internal Material	Spraying steel plate	
	External Material	Spraying steel plate	
Door	Electrically heated glass door*2		
Consumption	300W		
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)		
Casters	Yes		
Shelf	10		
Standard Accessory	Test hole, USB interface		
Optional Accessory	RS485, printer, temperature recorder		
Internal Size(W*D*H)	1100*454*1325mm	1100*479*1325mm	1100*684*1325mm
External Size(W*D*H)	1220*630*1885mm	1220*630*1885mm	1220*860*1885mm
Package Size(W*D*H)	1340*750*2100mm	1340*750*2100mm	1340*980*2100mm
Net Weight	189kg		212kg
Gross Weight	223kg		256kg