

Biological Microscope



Technical Parameters:

Model		BM-B100	BM-B101	BM-B102	BM-B103	BM-B104	BM-B105	BM-B106	BM-B108
Model									
Eyeiece	Wide Field Eyepieces WF10X (WF16X or H16X optional)	√	√	√	√	√	√	√	√
Viewing	Monocular	√	√	√	√	√	√	√	√
Head	Monocular with video teaching head	√	√	√	√	√	√	√	√
	Compensation free binocular head	√	√	√	√	√	√	√	√
	Compensation free trinocular head	√	√	√	√	√	√	√	√
Objective	4X (spring)	√	√	●	√	√	√	√	√
	10X(spring)	√	√	√	√	√	√	√	√
	40X (spring)	√	√	√	√	√	√	√	√
	100X(spring, oil)	●	√	√	√	√	√	√	√
Nosepiece	Triple Nosepiece	√	●	√	●	●	●	●	●
	Quadruple Nosepiece	●	√	●	√	√	√	√	√
Stage	Double layer mechanical stage, size:110*125mm	√	√	√	√	√	√	√	√
	Plain Stage with paired clips	√	√	●	√	●	√	●	√
	Plain Stage with moving scale	●	√	√	√	√	√	√	√
Focusing	Coaxial Coarse and Fine Adjustment, Focusing Range 20mm	√	√	√	√	√	√	√	√
Condenser	N.A.=1.25 Abbe condenser &Iris diaphragm (optional)	●	√	●	√	√	√	√	√
	N.A.=0.65 Abbe condenser &Iris diaphragm	√	√	√	√	●	√	●	√
Illumination	Electric light source LED	√	√	√	√	√	√	√	√
Diaphragm	Rotating disc diaphragm	●	√	√	√	√	√	√	√
Power Supply	AC Input 100~240V 50/60Hz, DC Output 12V	√	√	√	√	√	√	√	√
Package Size(W*D*H)mm		210*280*400			270*310*410				
Gross Weight(kg)		3	3.5	3.5	4	4	4.5	4.5	4.8

Note: √ Standard Outfit, ● Optional, \ Without this feature

Biological Microscope



Technical Parameters:

Model		BM-F101	BM-F102	BM-F103	BM-F104	BM-F105	BM-F106	BM-F108
Model								
Eyeiece	Wide Field Eyepieces WF10X(WF25X or WF20X or WF16X optional)	√	√	√	√	√	√	√
Viewing Head	Compensation Free Binocular Head				√	√		
	Dual Viewing Head, one Tube 30°							
	Inclined and Another Tube Vertical, 360° Rotatable		√	√				
	Compensation Free Trinocular Head						√	√
	Monocular	√						
Achromatic Objective	4X,10X,40X(Spring),100X (Spring, Oil)(185)	√	√	√	√	√	√	√
	4X,10X,40X (Spring), 100X (Spring, Oil)(195)	●	●	●	●	●	●	●
Nosepiece	Triple Nosepiece	●	●	●	●	●	●	●
	Quadruple Nosepiece	√	√	√	√	√	√	√
Stage	Double Layer Mechanical Stage, Size:110*125mm	√		√		√		√
	Plain Stage with Moving Scale		√		√		√	
Focusing	Coaxial Coarse and Fine Adjustment, Focusing Range 20mm	√	√	√	√	√	√	√
Condenser	Simple N. A=1.25 Abbe Condenser &Iris Diaphragm		√		√		√	
	Handwheel Adjustment							
	N.A=1.25 Abbe Condenser & Iris Diaphragm	√		√		√		√
Illumination	No Strobe High Brightness LED Light	√	√	√	√	√	√	√
Power Supply	AC Input 100~240V 50/60Hz,DC Output 12V	√	√	√	√	√	√	√
Package Size(W*D*H) mm		270*310*410						
Gross Weight(kg)		4	4	4.2	4.5	5	5	5.2

Note: √ Standard Outfit, ● Optional