

Laboratory Refrigerator




Technical Parameters

Model	BPR-5V1500
Capacity	1500L
Temp. Range	2~8℃
Temp. Accuracy	0.1℃
Temp. Uniformity	≤3℃
Temp. Stability	±3℃
Recovery Time (Recover to 8℃ in an ambient temp. of 32℃)	8min
Cooling Time (Cool down to 6℃ in an ambient temp. of 32℃)	30min
Control System	Microprocessor control
Display	LED
Alarm	High and low temperature alarm, sensor failure alarm, power failure alarm, opening and closing abnormal alarm
Refrigeration Type	Air-cooling
Refrigerant	R134a/620g
Compressor	International famous brand compressor/1
Condenser & Evaporator	Copper tube aluminum plate
Defrost	Automatic defrost
Construction	Polyurethane cyclopentane insulation material
Material	Internal Material: Spraying steel plate External Material: Spraying steel plate
Door	Electrically heated glass door*3
Consumption	537W
Power Supply	AC 220V, 50/60Hz(Standard); 110V, 50/60Hz(Optional)
Casters	Yes
Shelf	12
Standard Accessory	/
Optional Accessory	Test hole, USB interface, RS485, printer, temperature recorder
Internal Size(W*D*H)	1680*640*1420mm
External Size(W*D*H)	1800*775*1965mm
Package Size(W*D*H)	1340*750*2100mm
Net Weight	245kg
Gross Weight	280kg


-20/25℃ Freezer(Economic Type)



BDF-20V40



BDF-25V230



BDF-25V300

Technical Parameters

Model	BDF-20V40		BDF-25V230	BDF-25V300
Capacity	40L		230L	300L
Temp. Range	-10~-20℃		-10~-25℃	
Temp. Accuracy	1℃			
Temp. Uniformity	≤3℃			
Temp. Stability	≤3℃			
Control System	Microprocessor control			
Display	LED			
Alarm	High and low temperature alarm, thermostat fault alarm, door switch alarm			
Refrigeration Type	Direct-cooling			
Refrigerant	R600a/40g		R600a/64g	R600a/80g
Compressor	International famous brand compressor /1			
Condenser & Evaporator	Bundy tube, side plate type; aluminum tube, wound tube type		Bundy tube, side plate type; wire, tube type	
Defrost	Manual defrost		Automatic/Manual defrost	
Construction	Polyurethane cyclopentane foam			
Material	Internal Material	HIPS		
	External Material	Precoated steel plate		
Door	1/Cyclopentane monolithic foam door			
Consumption	90W		110W	120W
Power Supply	AC 220V, 50Hz(Standard); 220V, 60Hz, 110V, 60Hz(Optional, external transformer)			
Casters	No			
Adjustable Shelves/ Drawer	1		6	8
Standard Accessory	Test hole, shelf			
Internal Size (W*D*H)	400*295*426mm		410*440*1330mm	410*440*1700mm
External Size (W*D*H)	480*460*585mm		595*600*1565mm	595*600*1965mm
Package Size (W*D*H)	520*520*710mm		640*660*1770mm	640*660*2140mm
Net Weight	18kg		60kg	77kg
Gross Weight	26kg		75kg	93kg