

Electronic & Digital Hot Plate

Application:

It applies in drying articles in chemical analysis, physical determination, heat treatment and other temperature experiments in laboratories of industrial mining enterprise, medicine and health, environmental protection, biochemistry and scientific research and college labs etc.



Electronic Hot Plate(SSH-E Series)

Digital Hot Plate (SSH-D Series)

Features:

- * PID controller
- * Totally enclosed high quality stamping cold-rolled steel heating plate, with no open fire.
- * SSH-E type, adopts electric temperature control, could adjust temperature.
- SSH-D type, with LCD display, easy to observe and control temperature.
- * Control style: SSH-E electric type SSH-D digital type.

Technical Parameters:

Model	SSH-E400	SSH-E450	SSH-E600	SSH-D400	SSH-D450	SSH-D600
Plate Size	400*280mm	450*350mm	600*400mm	400*280mm	450*350mm	600*400mm
Range of Temperature	RT+20~380°C					
Material (Main body)	Cold-rolled steel with anti-bacteria powder coating					
Work Plate Material	Stainless steel					
Power Supply	AC220V,50/60HZ					
Consumption	1500W	2000W	3000W	1500W	2000W	3000W
Package Size(W*D*H)mm	430*330*230	470*410*230	620*460*230	450*330*290	500*400*290	550*450*290
Gross Weight(kg)	15.5	19.8	28.6	15.5	19.8	28.6

Heating Mantle

Several Rows Electronic Control Heating Mantles



HMD-III(LED Display)

HME-III

Features:

- * Corrosion-resisting and ageing-resistant
- * The internal heater is in hemisphere shape with high efficiency.
- * The external material is cold-rolled steel with anti-bacteria powder coating.
- * It adopts high-temperature resistant alkali-free glass fiber with good isolation performance.

Technical Parameters:

Model	Rows	Capacity (ml)	Max. Use Temp.	Working Time	Consum-ption(W)	Power Supply	External Size (W*D*H) mm	Packing Size (W*D*H) mm	Net Weight	Gross Weight
HME-III / HMD-III (LED Display)	Two rows	100	380°C	Contin-uous	360	AC110/220V±10%, 50/60Hz	300*290*150	360*340*180	3.7kg	4.5kg
		250			360		300*290*150	360*340*180	3.8kg	4.5kg
		500			500		300*290*150	360*340*180	5.2kg	5.8kg
		1000			600		390*355*150	470*390*180	6.9kg	7.5kg
	Four rows	100			720		600*290*150	670*330*180	7.25kg	9.1kg
		250			720		600*290*150	670*330*180	7.3kg	9.1kg
		500			1000		600*290*150	670*330*180	10kg	10.7kg
		1000			1200		780*350*150	800*390*180	14kg	14.8kg
	Six rows	100			1080		900*295*150	980*340*180	12kg	13.4kg
		250			1080		900*295*150	980*340*180	14.2kg	15kg
		500			1500		900*295*150	1100*310*300	14kg	15.3kg
		1000			1800		1170*355*150	1250*455*260	20kg	21kg