

## Vertical Autoclave



Basket(standard)

Mesh bottom  
basket(optional)

Bucket(optional)



Printer(optional)

### Technical Features:

- \* The flip-up quick-open door structure opens the cover quickly and labor-saving.
- \* Universal wheels are installed on the base of the machine to facilitate the movement and adjustment of the machine.
- \* It has a quick maintenance window, and the electrical part does not need to remove the cover for maintenance.
- \* Steam generation method: heating inside the main body, no external steam source is required.

- \* There are optional programs for exposed instruments, packaging instruments, rubber, dressings, solid customization and non-solid customization.
- \* Self-expanding silicone sealing ring has good sealing effect and long service life. It is molded with transparent medical silicone.
- \* Real-time detection and display of the temperature in the sterilization chamber, with a display accuracy of 0.1°C.
- \* The LED digital tube displays temperature, time, alarm code, and the indicator light indicates the current operating status.
- \* Use single-chip microcomputer control, heating, sterilization, and exhaust. Automatic control, no excessive manual operation.
- \* Use gravity displacement and positive pressure pulsation exhaust to exhaust the cold air in the load and sterilization room.
- \* Directly add water to the pot manually, and the entire sterilization process saves more time. The sterilization cycle ends with a buzzer prompt.
- \* An optional printer can be equipped to record the temperature during the sterilization process.
- \* A variety of programs  
There are exposed program, packaging program, rubber program, dressing program, liquid program, liquid customization and solid customization.

### Technical Parameters:

Model	BKQ-Z30I	BKQ-Z50I	BKQ-Z75I	BKQ-Z100I
Capacity	30L	50L	75L	100L
Designed Pressure	0.28MPa			
Working Pressure	0.23MPa			
Designed Temp.	150°C			
Working Temp.	105~136°C			
Temp. Precision	0.1°C			
Chamber Material	S30408			
Chamber Size	φ385*412mm	φ385*515mm	φ385*715mm	φ385*875mm
Basket/ Mesh Bottom	φ365*265mm, 1pc	φ365*360mm, 1pc	φ365*265mm, 2pcs	φ365*360mm, 2pcs
Basket/ Bucket				
Noise	≤65dB			
Altitude	≤2700m			
Standard Accessory	Basket			
Optional Accessories	Printer, mesh bottom basket, bucket			
Consumption	4KW			
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional)			
External Size(W*D*H)	645*610*710mm	645*610*810mm	645*610*945mm	645*610*1150mm
Net Weight	86kg	91kg	98kg	112kg
Packing Size(W*D*H)	750*745*950mm	750*745*1100mm	750*745*1240mm	750*745*1450mm
Gross Weight	102kg	105kg	116kg	124kg